

## Cincinnati/Northern Kentucky International Airport Fire Department

## **Cutting – Welding – Hot Work – Open Burning Permit**

**Important – Precautions On Reverse Side Must Be Observed** 

Date:	Job Number:
Location:	
Work Being Done:	
Permit Issued:	Permit Expires:
The precautions on the reverse side have been completed. Permission has been granted by the Airport Fire Department for this work. Any deviation from checked precautions on reverse side may cause the Airport Fire Department to stop the operation.	
Responsible Party/Agency:	
Signature:	
Airport FD Representative or KCAB Supervisor	or:

## In case of fire call 911 or 3111 Absolutely NO SMOKING on the ramp

Do not cut, weld, use open flame, spark producing equipment, or per-form open burning until the following precautions have been taken:

PRECAUTIONS:
Flame or sparks producing equipment has been inspected and found in good repair.
Sprinkler system in service.
Proper safety equipment for welder.
WITHIN 35 FT. OF WORK:
Floors swept and clear of all possible combustibles.
Combustible floors protected.
All combustible and flammable materials removed.
Combustible and Flammable liquids moved or covered with metal shield.
All walls and floor openings covered.
Cover suspended beneath work to collect sparks and slag.
WALLS, CEILINGS AND ROOFS:  Combustibles moved away from opposite side of wall, ceiling or roof.  Precautions shall be taken when welding on pipes thru wall.  Plug holes where slag and sparks may pass thru.
FUEL TRUCKS AND TANKS:
Equipment cleaned of all combustibles.
Containers purged of flammable vapors/liquids.
Pressurized vessels, piping and equipment removed from service, isolated and vented.
FIRE WATCH:
To be provided for no less than 1 hour after operation.
1 ABC fire extinguisher for every welding operation.

All welding operations at the Cincinnati/Northern Kentucky International Airport shall conform to N.F.P.A. 51B. Any deviation may cause the Airport Fire Department to stop the operation.