

SIRIUS ENERGY STORAGE MODULE
TECHNICAL DATA SHEET
Part Number: 3550-48-A-1.7C-M-A-G
Version Date: 08-16-18

| | |
|--|--|
| Nominal Voltage | 48VDC |
| Voltage Range | 44VDC – 54VDC |
| Capacity | 3550Wh |
| Maximum Charge Rate (0% -100% SOC) | 125A |
| Maximum Discharge Rate (100% - 0% SOC) | 125A |
| Maximum Charging Voltage | 54VDC |
| Internal Resistance | ≤4mΩ |
| Supercap cell DC to DC Roundtrip efficiency (@125A) | 99.1% |
| Supercap cell Operating Temperature ¹ | -30°C to 85°C |
| Galvanic Isolation | 1500V |
| Projected Cycle Life ^{2,3} | 1,000,000 |
| Projected Calendar Life ^{3,4} | 45 years |
| Shelf Life ⁵ | 10 years |
| Warehousing | Can be stored at any SOC without affecting cycle life |
| Communication Port | TCP/IP RJ45 Ethernet |
| Monitoring Data | Temperature, Voltage, Current, Energy, Supercap Balancing |
| Remote Control Input | Battery Self-Check |
| Terminal Type | F12 |
| Module Casing Material | Aluminium |
| Dimensions module/packed (w x d x h) | 600mm x 534mm x 200mm/680mm x 615mm x 280mm |
| Weight module/packed | 69kg/73kg |
| Supercap Cell Self discharge ⁶ | 2% per month |
| Alarm | Audible alarm in the event of Over-Charge, Over-Discharge, Over-Temperature, Over-Current |
| CE Certification ⁷ | EN55032:2015, EN55024:2010, EN61000-4-2:2009, EN61000-4-3:2006+A1:2008+A2:2010 |
| Precautions | |
| Alarm | In case of alarm, immediately rectify / attend to the cause of the alarm |
| Physical Damage | In case the module is physically damaged due to any event, do not install and energize the module under any circumstances and contact an authorized technician |
| Short Circuit | Ensure precautions to prevent short-circuit under all circumstances |
| Galvanic isolation | When connecting to external devices ensure that galvanic isolation does not exceed 1500V |
| Charge / Discharge Current | Under no circumstances must the charge / discharge current exceed 125A |
| Charging Voltage | Under no circumstances must the charging voltage exceed 54VDC for more than 60 seconds. |
| Charge Cycle | During charge cycle ensure never to exceed constant voltage of 54VDC and constant current of 125A |
| Series Connection | All modules must be at 100% SOC before connecting in series |
| Maximum number of modules that can be connected in series ⁸ | Eight with Module Combiner |

This technical data sheet may change without notice and at the sole discretion of Kilowatt Labs, Inc.



SIRIUS ENERGY STORAGE MODULE
TECHNICAL DATA SHEET
Part Number: 3550-48-A-1.7C-M-A-G
Version Date: 08-16-18

| | |
|---|---|
| | Please consult with Kilowatt Labs or its Reseller when connecting the modules in series. Under no circumstances should more than three modules be connected in series without the Module Combiner |
| Maximum number of modules that can be connected in parallel | No limit |
| Series – Parallel Connection | Modules cannot be connected in a series – parallel combination under any circumstances |
| Sirius View – Monitoring Software | |
| Individual Cell | Monitoring of voltage |
| Module | Monitoring of current, max. & min. voltage, temperature, DOD, SOC, rate of charge, rate of discharge, time to discharge, balance energy, total energy delivered over lifetime, graphs |
| System | Monitoring of all modules connected together |

¹Cycle life may vary if the module is to be operated continuously outside a temperature range of -10°C to 55°C, and/or at C-rates higher than the maximum charge/discharge rate specified in this spec sheet. Please consult Kilowatt Labs or its Reseller prior to deploying the module in such applications.

²Projected Cycle life of supercap cells.

³Additional terms and conditions, including a limited warranty, will apply at the time of purchase.

⁴Projected Calendar life of supercap cells from the date of first operation

⁵Shelf life is the life of the module (in years) from the date it is manufactured to the time it is first operated

⁶Self-discharge for the module is 2% per month if idle (not charging or discharging) AND in Sleep Mode (switched off). If the module is not in sleep mode, then self-discharge may vary depending on ambient temperature.

⁷CE certification is completed for supercap cells

⁸Consult Kilowatt labs or its Reseller for information on connecting modules in series.

Product dimensions are for reference only unless otherwise identified and may change without notice. For critical applications, please contact Kilowatt Labs, Inc., or its Reseller.