



WARNING LIGHTING

DIRECTIONAL LIGHTING

LIGHTBARS

WHITE LIGHTING

REVERSING SAFET



# **ALARMS**



# **800 Series**Reversing Alarms

Designed to meet all the harsh operational requirements of any fleets equipment, ECCO's 800 Series alarms feature a reverse-mounted speaker design and reinforced nylon housing providing unrivaled durability. These alarms are so robust that an ECCOLIFE<sup>TM</sup> warranty covering the alarm for the life of the vehicle is offered on all models. Smart Alarm® models measure ambient noise and adjust their sound level, creating a volume that is safe without being annoying or contributing to noise pollution. Smart Alarms eliminate the need for constant manual adjustment and help prevent intentional alarm disconnection.


## **Models**

PART NO.	TYPE	VOLTAGE	dB(A)	<b>AMPS</b>	APPROVALS
917N-001	Smart	12-24	87-112	1.5	SAE Type F, CE, R10
830N-001	-	12-36	107	1.1	SAE Type B, CE, R10, AMECA
850N-001	-	12-36	112	1.3	SAE Type A, CE, R10, UL, AMECA

#### **Features and Benefits**

- Reverse mounted speaker enhances sound and protects the speaker from dust and moisture ingress
- Reinforced nylon housing eliminates corrosion damage
- Sealed in epoxy for protection against dust, moisture and vibration
- Steam cleanable and pressure washable
- Temperature Range: -40°C to +85°C

#### **Dimensions**



## **Alarm Specifications**

Connection: 16 AWG blunt cut wires Reinforced nylon housing Recommended mounting bolt: Bottom: 3/8-16 UNC Grade 5 or better Back: 5/16-18 UNC Grade 5 or better

Recommended washer: Bottom: 3/8" Type A Series N washer Back: 5/16" Type A Series N washer

Recommended mounting torque: Bottom: 276 in. lbs. Back: 156 in. lbs.

+44 (0)113 237 5340 | sales@eccogroup.com