



## Light Cut Mini LED

Knife-edge interior cove system for interior architecture

### Description

The Light Cut Mini is a linear cove lighting system comprising an knife-edge extruded profile which integrates perfectly in drywall ceilings. The spot modules are 3-ct track mounted and slide along the profile for maximum flexibility. A cove housing is created on the jobsite by the contractors. The system is available in two sizes depending on the installation. It has accessories for visual comfort optimization and color filters. The system can be utilized for as a cove in the middle of the ceiling or perimeter channels.



### Lamp

|                   |                       |
|-------------------|-----------------------|
| System Lamp Type  | Power LED / LED Array |
| Color Temperature | 3000K                 |
| Color Rendering   | CRI80 / CRI90         |
| Application       | General Lighting      |

### Spot Modules

LED Array

Power LED



### Physical

|                           |  |
|---------------------------|--|
| Material                  | Extruded Aluminum  |
| Ingress Protection Rating | IP20   |
| Finishes                  | <input type="checkbox"/> 30 = White <input checked="" type="checkbox"/> 14 = Black |



### Certifications



### Photometrics

For current IES files please visit [arch.flosusa.com](http://arch.flosusa.com)

### Warranty

2 years from date of sale.

|                   |         |
|-------------------|---------|
| Installation type | Surface |
| Environment       | Indoor  |
| Field cuttable    | Yes     |

### Electrical & Control

|                      |   |
|----------------------|---|
| Driver location      | Integral                                    |
| Driver Input Voltage | 120V-277V                                   |
| Control              | Electronic dimmable ELV, dims all in unison |



## Light Cut Mini LED

Knife-edge interior cove system for interior architecture

### Notes

Profile is available for 5/8" or 1/2" drywall applications.

System available in two standard openings: 2.8" and 5.5".



Listings: UL Listed, IP20 dry rated only.



### Spot Modules

LED Array

Power LED



### Certifications



### Photometrics

For current IES files please visit [arch.flosusa.com](http://arch.flosusa.com)

### Warranty


2 years from date of sale.

## Light Cut Mini LED

Knife-edge interior cove system for interior architecture

### Channel 2.75" [70mm] Profile

Light Cut Mini 2.75" [70mm] Aluminum profile is adapted to 5/8" ceiling thickness.




### How to Specify ex. 08.8720.14.90

| Length      | Part Number for Aluminum profile (2 unit per code) | Finish  | Ceiling thickness |
|-------------|--|---|-------------------|
| 39.75" (1m) | 08.8720  | <input type="checkbox"/> 30 = White<br><input checked="" type="checkbox"/> 14 = Black | .90 = 5/8"        |
| 78.74" (2m) | 08.8721  |   |                   |

### Channel 2.75" [70mm] Corner

Light Cut Mini 2.75" [70mm] Aluminum Corner for 5/8" Ceiling




### How to Specify ex. 08.8707.14.90

| Length                          | Part Number for Aluminum corner | Finish  | Ceiling thickness |
|---------------------------------|---------------------------------|---|-------------------|
| 12.32" x 12.32" (313mm x 313mm) | 08.8707                         | <input type="checkbox"/> 30 = White<br><input checked="" type="checkbox"/> 14 = Black | .90 = 5/8"        |

### Channel 2.75" [70mm] End Cap

Light Cut Mini 2.75" [70mm] Aluminum End Cap for 5/8" Ceiling



### How to Specify ex. 08.8705.14.90


| Aperture   | Part Number for Aluminum corner | Finish  | Ceiling thickness |
|------------|---------------------------------|---|-------------------|
| 2.75" [1m] | 08.8705                         | <input type="checkbox"/> 30 = White<br><input checked="" type="checkbox"/> 14 = Black | .90 = 5/8"        |

## Light Cut Mini LED

Knife-edge interior cove system for interior architecture

### Channel 5.51" [130mm] Profile

Light Cut Mini 5.51" [130mm] Aluminum profile is adapted to 5/8" ceiling thickness.




### How to Specify ex. 08.8720.14.90

| Length      | Part Number for Aluminum profile (2 unit per code) | Finish  | Ceiling thickness |
|-------------|--|---|-------------------|
| 39.75" (1m) | 08.8720  | <input type="checkbox"/> 30 = White<br><input checked="" type="checkbox"/> 14 = Black | .90 = 5/8"        |
| 78.74" (2m) | 08.8721  |   |                   |

### Channel 5.51" [140mm] Corner

Light Cut Mini 5.51" [140mm] Aluminum Corner for 5/8" Ceiling.




### How to Specify ex. 08.8708.14.90

| Length                          | Part Number for Aluminum corner | Finish  | Ceiling thickness |
|---------------------------------|---------------------------------|---|-------------------|
| 15.07" X 15.07" (383mm x 383mm) | 08.8708                         | <input type="checkbox"/> 30 = White<br><input checked="" type="checkbox"/> 14 = Black | .90 = 5/8"        |

### Channel 5.51" [140mm] End Cap

Light Cut Mini 5.5" [140mm] Aluminum End Cap for 5/8" Ceiling.



### How to Specify ex. 08.8706.14.90


| Aperture  | Part Number for Aluminum corner | Finish  | Ceiling thickness |
|-----------|---------------------------------|---|-------------------|
| 5.5" [1m] | 08.8706                         | <input type="checkbox"/> 30 = White<br><input checked="" type="checkbox"/> 14 = Black | .90 = 5/8"        |

Light Cut Mini LED

Knife-edge interior cove system for interior architecture

Perimeter Profile

Light Cut Mini Perimeter Aluminum Profile for 5/8" ceiling thickness.




How to Specify ex. 08.8701.14.90

Table with 4 columns: Length, Part Number for Aluminum profile (2 unit per code), Finish, and Ceiling thickness. It lists two options: 39.75" (1m) with part number 08.8701 and 78.74" (2m) with part number 08.8702. Both specify a ceiling thickness of .90 = 5/8".

Perimeter Corner Inner

Light Cut Mini 5.51" [140mm] Aluminum Corner for 5/8" Ceiling.




How to Specify ex. 08.8709.14.90

Table with 4 columns: Length, Part Number for Inner Corner Aluminum profile, Finish, and Ceiling thickness. It lists one option: 3.7" X 3.7" (93mm x 93mm) with part number 08.8709. Both specify a ceiling thickness of .90 = 5/8".

Perimeter Corner Outer

Light Cut Mini Perimeter Aluminum Profile Inner/Outer Corner, for 5/8" Ceiling.



How to Specify ex. 08.8710.14.90


Table with 4 columns: Length, Part Number for Outer Corner Aluminum profile, Finish, and Ceiling thickness. It lists one option: 5.9" X 5.9" (150mm x 150mm) with part number 08.8710. Both specify a ceiling thickness of .90 = 5/8".

Optional Profile Accessories

Vertical Corner Anchorage

Part Number:

08.8711.00




Light Cut Mini LED

Knife-edge interior cove system for interior architecture


Spot Modules

LED Spot Module developed to be installed in Light Cut Mini System.

Spot Module LED Array



Spot Module Power LED



How to Specify ex. 09.0220.30.UF

| Version               | CCT   | CRI | Initial Lumen | Delivered Lumen | Watts | Beam Spread | Part Number | Finish                   | Dimmable           |
|-----------------------|-------|-----|---------------|-----------------|-------|-------------|-------------|--------------------------|--------------------|
| Spot Module Power LED | 3000K | 80  | 1200 lm       | 648 lm          | 10W   | 13°         | 09.0220     | 30 = White               | DUF = ELV Dimmable |
|                       |       |     |               |                 |       |             |             | 14 = Black               |                    |
|                       |       |     | 1200 lm       | 373 lm          | 10W   | 41°         | 09.0221     | 30 = White               | DUF = ELV Dimmable |
|                       |       |     |               |                 |       |             |             | 14 = Black               | CUF = ELV Dimmable |
| Spot Module LED Array | 3000K | 90  | 1385 lm       | 1006 lm         | 14.4W | 28°         | 09.0217     | 30 = White<br>14 = Black | CUF = ELV Dimmable |
|                       |       |     | 1385 lm       | 969 lm          | 14.4W | 32°         | 09.0218     |                          |                    |
|                       |       |     | 1385 lm       | 959 lm          | 14.4W | 43°         | 09.0219     |                          |                    |
|                       |       |     |               |                 |       |             |             |                          |                    |

## Light Cut Mini LED

Knife-edge interior cove system for interior architecture

### Accessories for LED Array and Power LED

|   |  |  |  |
|---|--|--|--|
| Honeycomb   | Blue filter  | Sky blue filter  | Amber filter   |
| 08.3309.14  | 08.8501.64.0D  | 08.8501.65.0D  | 08.8501.66.0D  |
|    |   |   |   |
| Red filter  | Hot light  | Cold light   | Daylight   |
| 08.8501.67.0D   | 08.8501.69   | 08.8501.CL   | 08.8501.DL   |
|   |  |  |  |
| Neodimium   |  |  |  |
| 08.8501.ND  |  |  |  |
|  |  |  |  |

**Note:** For LED Array version non additional accessories are required