




## Dimensions



## Certifications



## Photometrics

For current IES files please visit  
[architectural.flosusa.com](http://architectural.flosusa.com)

## Warranty

2 years from date of sale.

FLOS. USA  
36 East 31st Street  
Suite 402  
New York N.Y. 10016  
(800) 841.4011

## Light Supply Fixed Trimmed

Ceiling Recessed Fixed Downlight

### Description

A range of compact LED downlights capable of up to 3000 lm output, specially designed for public spaces and retail installations. Offering a wide range of options, optics and accessories, the Light Supply is available in fixed, wall-washer and adjustable versions, as well as trimmed and trimless, making a complete family that can be used throughout a project for many different lighting needs.

### Lamp

Lamps Type	LED - Phosphor LED
Wattage	26W / 28W
Output Nominal	2285 lm, 3000 lm
Color Temperature	3000K, 4000K
Color rendering	CRI 98 / CRI 80

### Optical

Beam Angle	49° / 65°
Lighting Type	Direct
Light Distribution	Symmetric

### Physical


Aiming	Fixed
Weight	2.16 Lbs
Ingress Protection Rating	IP44

### Finishes


1B ■ 14 Black □ 40 White	1C ■ 14 Black ■ 06 Aluminium	3B □ 40 White □ 40 White	3C □ 40 White ■ 06 Aluminium
--------------------------------	------------------------------------	--------------------------------	------------------------------------



Installation type	Ceiling Recessed
Environment	Indoor dry location



## Dimensions



## Light Supply Fixed Trimmed

Ceiling Recessed Fixed Downlight

### Electrical & Control

Input Voltage	120-277V
Control	<ul style="list-style-type: none"> <li>• Standard 0-10V dimming 1% linear</li> <li>• ELV for .90 variant with housing</li> </ul>
Driver	Remote included

### Performance

Maximum delivered output	From 1158 lm up to 2270 lm
Efficacy	up to 81.07 lm/W

### Notes

Fixture comes with separate trimless installation frame which allows for installation in sheet rock and special construction ceilings up to 1/2" thick.

Trimless versions must be mounted in a standard pre-installation metal frame (shipped separately with product) or in a Soft Architecture technology installation plate for 1/2" thick ceilings.

Spot, medium and flood reflectors are available as accessories to change the light beam angle.

10.9" (277mm) minimum plenum height.

Housing details available upon request.

Listings: UL Listed, IP44 damp location.

Light Supply comes complete with driver and splice box.

## Certifications



JAB-2019 CA  
TITLE 24  
LISTED



## Photometrics

For current IES files please visit  
[architectural.flosusa.com](http://architectural.flosusa.com)


## Warranty

2 years from date of sale.

Light Supply Fixed Trimmed

Ceiling Recessed Fixed Downlight


How to specify



How to Specify ex. 03.6611.3C.U.L

Part Number	CCT	CRI	Initial Lumens	Watts	Beam Angle	Finish	Power Supply
03.6611	3000	98	2285	26W	65° 49°	<div> <div>1B= Black / White</div> <div>1C= Black / Aluminium</div> <div>3B= White / White</div> <div>3C= White / Aluminium</div> </div>	90 = Housing with LED driver 830mA, ELV, 120-277V UL = Splice Box, 1% Dim, 0-10V, 120V 7U = Splice Box, 1% Dim, 0-10V, 277V GT = Splice box, 10% dim, ELV, 120V
03.6610	4000	80	3000	28W	65° 49°	<div> <div>1B= Black / White</div> <div>1C= Black / Aluminium</div> <div>3B= White / White</div> <div>3C= White / Aluminium</div> </div>	90 = Housing with LED driver 830mA, ELV, 120-277V UL = Splice Box, 1% Dim, 0-10V, 120V 7U = Splice Box, 1% Dim, 0-10V, 277V GT = Splice box, 10% dim, ELV, 120V

Photometrics




Light Supply Fixed Trimmed

Ceiling Recessed Fixed Downlight

Optional Accesories

Registration tray -non electrical, place holder for non IC new construction,  $\varnothing$  6.19"


TRAY-0007



Required Accessory: Housing for Variant .90 SKU

Light Supply Housing for New construction. CCEA Chicago Plenum. Housing includes LED driver 830mA, ELV Phase Cut, 120-277V

08.8593.00.90



1 male, 1 female hanger bar Extendable from 14" to 24" centers. Qty required for housing is 2. Part number listed below is a Set of 2

08.1201.00.UL

