




Dimensions



Certifications



Photometrics

For current IES files please visit architectural.flosusa.com

Warranty

2 years from date of sale.

FLOS. USA
36 East 31st Street
Suite 402
New York N.Y. 10016
(800) 841.4011

Light Supply Adjustable Trimless

Ceiling Recessed Adjustable Downlight

Description

A range of compact LED downlights capable of up to 3000 lm output, specially designed for public spaces and retail installations. Offering a wide range of options, optics and accessories, the Light Supply is available in fixed, wall-washer and adjustable versions, as well as trimmed and trimless, making a complete family that can be used throughout a project for many different lighting needs.

Lamp

Lamps Type	LED Array
Wattage	26W / 28W
Output Nominal	2285 lm, 3000 lm
Color Temperature	3000K, 4000K
Color rendering	CRI 98 / CRI 80

Optical

Beam Angle	16° / 24° / 33°
Lighting Type	Direct
Light Distribution	Symmetric

Physical

Aiming	Adjustable
Weight	2.22 Lbs
Ingress Protection Rating	IP23

Finishes

- 40 White 14 Black



Installation type	Ceiling Recessed
Environment	Indoor dry location



Light Supply Adjustable Trimless

Ceiling Recessed Adjustable Downlight


Electrical & Control

Input Voltage	120-277V
Control	<ul style="list-style-type: none"> • Standard 0-10V dimming 1% linear • ELV for .90 variant with housing
Driver	Remote included

Performance

Maximum delivered output	From 1292 lm up to 1871 lm
Efficacy	up to 66.82 lm/W

Dimensions



Notes

Trimless versions must be mounted in a standard pre-installation metal frame (shipped separately with product) or in a Soft Architecture technology installation plate for 1/2" dry ceilings

Spot, medium and flood reflectors are available as accessories to change the light beam angle without needing to dismount the fixture from the ceiling

Factory recommends 9.4" (239mm) minimum plenum height

Housing details available upon request

Listings: UL Listed, IP23 dry location only

Maximum tilt angle 35°

Maximum rotation 365°

Certifications



JAB-2019 CA
TITLE 24
LISTED



Photometrics

For current IES files please visit
architectural.flosusa.com


Warranty

2 years from date of sale.

Light Supply Adjustable Trimless

Ceiling Recessed Adjustable Downlight


How to specify



How to Specify ex. 03.6621.40.U.L

Table with 8 columns: Part Number, CCT, CRI, Initial Lumens, Watts, Beam Angle, Finish, and Power Supply. It lists specifications for two CCT options (3000K and 4000K) across different beam angles (16°, 24°, 33°) and finishes (40 White, 14 Black).

Photometrics



Light Supply Adjustable Trimless

Ceiling Recessed Adjustable Downlight

Required Accesories

Pre-installation frame Light Supply Adjustable Trimless.



08.8119.00.90



Optional Accesories

Registration tray -non electrical, place holder for non IC new construction, Ø 6.19"



TRAY-0007



Required Accessory: Housing for Variant .90 SKU

Light Supply Housing for New construction. CCEA Chicago Plenum. Housing includes LED driver 830mA, ELV Phase Cut, 120-277V

08.8593.00.90



1 male, 1 female hanger bar Extendable from 14" to 24" centers. Qty required for housing is 2. Part number listed below is a Set of 2

08.1201.00.UL

