



## Light Supply Fixed Trimless

Ceiling Recessed Fixed Downlight


### Description

A range of compact LED downlights capable of up to 3000 lm output, specially designed for public spaces and retail installations. Offering a wide range of options, optics and accessories, the Light Supply is available in fixed, wall-washer and adjustable versions, as well as trimmed and trimless, making a complete family that can be used throughout a project for many different lighting needs.

### Lamp

Lamps Type	LED - Phosphor LED
Wattage	26W / 28W
Output Nominal	2285 lm, 3000 lm
Color Temperature	3000K, 4000K
Color rendering	CRI 98 / CRI 80

### Dimensions



### Optical

Beam Angle	49° / 65°
Lighting Type	Direct
Light Distribution	Symmetric

### Physical

Aiming	Fixed
Weight	0.98 Lbs
Ingress Protection Rating	IP44

### Finishes



### Certifications



### Photometrics

For current IES files please visit [architectural.flosusa.com](http://architectural.flosusa.com)

### Warranty

2 years from date of sale.

Installation type	Ceiling Recessed
Environment	Indoor dry location



## Light Supply Fixed Trimless

Ceiling Recessed Fixed Downlight




### Electrical & Control

<b>Input Voltage</b>	120-277V
<b>Control</b>	<ul style="list-style-type: none"> <li>• Standard 0-10V dimming 1% linear</li> <li>• ELV for .90 variant with housing</li> </ul>
<b>Driver</b>	Remote included

### Performance

<b>Maximum delivered output</b>	From 1487 lm up to 1696 lm
<b>Efficacy</b>	up to 60,5 lm/W

### Dimensions



### Notes

Trimless versions must be mounted in a standard pre-installation metal frame (shipped separately with product) or in a Soft Architecture technology installation plate for 1/2" thick ceilings.

Spot, medium and flood reflectors are available as accessories to change the light beam angle.

10.9" (277mm) minimum plenum height.

Housing details available upon request.

Listings: UL Listed, IP44 damp location.

Light Supply comes complete with driver and splice box.

### Certifications



JAB-2019 CA  
TITLE 24  
LISTED



### Photometrics

For current IES files please visit [architectural.flosusa.com](http://architectural.flosusa.com)


### Warranty

2 years from date of sale.

## Light Supply Fixed Trimless

Ceiling Recessed Fixed Downlight

### How to specify





#### How to Specify

ex. 03.6625.40.UL



Part Number	CCT	CRI	Initial Lumens	Watts	Beam Angle	Finish	Power Supply
03.6625	4000	80	1696	28W	65°	<input type="checkbox"/> 40 = White	90 = Housing with LED driver 830mA, ELV, 120-277V UL = Splice Box, 1% Dim, 0-10V, 120V 7U = Splice Box, 1% Dim, 0-10V, 277V GT = Splice box, 10% dim, ELV, 120V
			2270		49°	<input checked="" type="checkbox"/> 06 Aluminium	
03.6626	3000	98	1158	26W	65°	<input type="checkbox"/> 40 = White	90 = Housing with LED driver 830mA, ELV, 120-277V UL = Splice Box, 1% Dim, 0-10V, 120V 7U = Splice Box, 1% Dim, 0-10V, 277V GT = Splice box, 10% dim, ELV, 120V
			1576		49°	<input checked="" type="checkbox"/> 06 Aluminium	

### Photometrics

#### 3000K



#### 4000K



## Light Supply Fixed Trimless

Ceiling Recessed Fixed Downlight

### Required Accesories

Pre-installation frame Light Supply Fixed Trimless.



08.8359.00.90



### Optional Accesories

Registration tray -non electrical, place holder for non IC new construction,  $\varnothing$  6.19"


TRAY-0007



### Required Accessory: Housing for Variant .90 SKU

Light Supply Housing for New construction. CCEA Chicago Plenum. Housing includes LED driver 830mA, ELV Phase Cut, 120-277V

08.8593.00.90



1 male, 1 female hanger bar Extendable from 14" to 24" centers. Qty required for housing is 2. Part number listed below is a Set of 2

08.1201.00.UL

