



## Light Supply Wall Washer Trimmed

Ceiling Recessed Trimmed Wall Wash


### Description

A range of compact LED downlights capable of up to 3000 lm output, specially designed for public spaces and retail installations. Offering a wide range of options, optics and accessories, the Light Supply is available in fixed, wall-washer and adjustable versions, as well as trimmed and trimless, making a complete family that can be used throughout a project for many different lighting needs.

### Lamp

Lamps Type	LED - Phosphor LED
Wattage	26W / 28W
Output Nominal	2285 lm, 3000 lm
Color Temperature	3000K, 4000K
Color rendering	CRI 98 / CRI 80

### Dimensions



### Optical

Beam Angle	38° / 35°
Lighting Type	Direct
Light Distribution	Asymmetric

### Physical

Aiming	Fixed
Weight	2.22 Lbs
Ingress Protection Rating	IP44

### Finishes

- |  |   |   |  |
|--|---|---|--|
| <b>1B</b><br><input checked="" type="checkbox"/> 14 Black<br><input type="checkbox"/> 40 White | <b>1C</b><br><input checked="" type="checkbox"/> 14 Black<br><input checked="" type="checkbox"/> 06 Aluminium | <b>3B</b><br><input type="checkbox"/> 40 White<br><input type="checkbox"/> 40 White | <b>3C</b><br><input type="checkbox"/> 40 White<br><input checked="" type="checkbox"/> 06 Aluminium |
|--|---|---|--|



### Certifications



JAB-2019 CA  
 TITLE 24  
 LISTED



### Photometrics

For current IES files please visit [architectural.flosusa.com](http://architectural.flosusa.com)

### Warranty

2 years from date of sale.

Installation type	Ceiling Recessed
Environment	Indoor dry location



## Light Supply Wall Washer Trimmed

Ceiling Recessed Trimmed Wall Wash


### Electrical & Control

<b>Input Voltage</b>	120-277V
<b>Control</b>	<ul style="list-style-type: none"> <li>• Standard 0-10V dimming 1% linear</li> <li>• ELV for .90 variant with housing</li> </ul>
<b>Driver</b>	Remote included

### Performance

<b>Maximum delivered output</b>	1354 lm / 1967 lm
<b>Efficacy</b>	up to 70.25 lm/W

### Dimensions



### Notes

Fixture comes with separate trimless installation frame which allows for installation in sheet rock and special construction ceilings up to 1/2" thick.

No Trim versions must be mounted in a standard pre-installation metal frame or in a Soft Architecture technology installation frame for 1/2" thick ceilings.

Spot, medium and flood reflectors are available as accessories to change the light beam angle without needing to dismount the fixture from the ceiling.

11.4" (290mm) minimum plenum height.

Listings: UL Listed, IP44 damp location.

### Certifications



JAB-2019 CA  
TITLE 24  
LISTED



### Photometrics

For current IES files please visit [architectural.flosusa.com](http://architectural.flosusa.com)


### Warranty

2 years from date of sale.

## Light Supply Wall Washer Trimmed

Ceiling Recessed Trimmed Wall Wash

### How to specify





#### How to Specify

ex. 03.6614.3C.U.L



Part Number	CCT	CRI	Initial Lumens	Watts	Beam Angle	Finish	Power Supply
03.6614	3000	98	2285	26W	38° 35°	<ul style="list-style-type: none"> <li>■ 1B= Black / White</li> <li>■ 1C= Black / Aluminium</li> <li>■ 3B= White / White</li> <li>■ 3C= White / Aluminium</li> </ul>	90 = Housing with LED driver 830mA, ELV, 120-277V UL = Splice Box, 1% Dim, 0-10V, 120V 7U = Splice Box, 1% Dim, 0-10V, 277V GT = Splice box, 10% dim, ELV, 120V
03.6613	4000	80	3000	28W	37° 35°	<ul style="list-style-type: none"> <li>■ 1B= Black / White</li> <li>■ 1C= Black / Aluminium</li> <li>■ 3B= White / White</li> <li>■ 3C= White / Aluminium</li> </ul>	90 = Housing with LED driver 830mA, ELV, 120-277V UL = Splice Box, 1% Dim, 0-10V, 120V 7U = Splice Box, 1% Dim, 0-10V, 277V GT = Splice box, 10% dim, ELV, 120V

### Photometrics

#### 3000K



#### 4000K




## Light Supply Wall Washer Trimmed

Ceiling Recessed Trimmed Wall Wash

### Optional Accesories

Registration tray -non electrical, place holder for non IC new construction,  $\varnothing$  6.19"


#### TRAY-0007



### Required Accessory: Housing for Variant .90 SKU

Light Supply Housing for New construction. CCEA Chicago Plenum. Housing includes LED driver 830mA, ELV Phase Cut, 120-277V

#### 08.8593.00.90



1 male, 1 female hanger bar Extendable from 14" to 24" centers. Qty required for housing is 2. Part number listed below is a Set of 2

#### 08.1201.00.UL

