



Light Supply Wall Washer Trimless

Ceiling Recessed Trimless Fixed Wall-Wash


Description

A range of compact LED downlights capable of up to 3000 lm output, specially designed for public spaces and retail installations. Offering a wide range of options, optics and accessories, the Light Supply is available in fixed, wall-washer and adjustable versions, as well as trimmed and trimless, making a complete family that can be used throughout a project for many different lighting needs.

Lamp

Lamps Type	LED - Phosphor LED
Wattage	26W / 28W
Output Nominal	2285 lm, 3000 lm
Color Temperature	3000K, 4000K
Color rendering	CRI 98 / CRI 80

Dimensions



Optical

Beam Angle	38° / 35°
Lighting Type	Direct
Light Distribution	Asymmetric

Physical

Aiming	Fixed
Weight	0.98 Lbs
Ingress Protection Rating	IP44

Finishes

- | | |
|-----------------------------------|--------------------------------------------------|
| 3B | 3C |
| <input type="checkbox"/> 40 White | <input type="checkbox"/> 40 White |
| <input type="checkbox"/> 40 White | <input checked="" type="checkbox"/> 06 Aluminium |



Certifications



Photometrics

For current IES files please visit architectural.flosusa.com

Warranty

2 years from date of sale.

Installation type	Ceiling Recessed
Environment	Indoor dry location



Light Supply Wall Washer Trimless

Ceiling Recessed Trimless Fixed Wall-Wash


Electrical & Control

Input Voltage	120-277V
Control	<ul style="list-style-type: none"> • Standard 0-10V dimming 1% linear • ELV for .90 variant with housing
Driver	Remote included

Performance

Maximum delivered output	From 1354 lm up to 1967 lm
Efficacy	up to 70.25 lm/W

Dimensions



Notes

No Trim versions must be mounted in a standard pre-installation metal frame (shipped separately with product) or in a Soft Architecture technology installation frame for 1/2" thick ceilings.

Spot, medium and flood reflectors are available as accessories to change the light beam angle.

Factory suggests 11.4" (290mm) minimum plenum height.

Housing details available upon request.

Listings: UL Listed, IP44 damp location.

Certifications



JAB-2019 CA
TITLE 24
LISTED



Photometrics

For current IES files please visit architectural.flosusa.com


Warranty

2 years from date of sale.

Light Supply Wall Washer Trimless

Ceiling Recessed Trimless Fixed Wall-Wash

How to specify





How to Specify

ex. 03.6628.40.U.L



Part Number	CCT	CRI	Initial Lumens	Watts	Beam Angle	Finish	Power Supply
03.6628	4000	80	3000	28W	35°	<input type="checkbox"/> 40 White <input checked="" type="checkbox"/> 06 Aluminium	90 = Housing with LED driver 830mA, ELV, 120-277V UL = Splice Box, 1% Dim, 0-10V, 120V 7U = Splice Box, 1% Dim, 0-10V, 277V GT = Splice box, 10% dim, ELV, 120V
03.6629	3000	98	2285	26W	38°	<input type="checkbox"/> 40 White <input checked="" type="checkbox"/> 06 Aluminium	90 = Housing with LED driver 830mA, ELV, 120-277V UL = Splice Box, 1% Dim, 0-10V, 120V 7U = Splice Box, 1% Dim, 0-10V, 277V GT = Splice box, 10% dim, ELV, 120V

Photometrics

3000K



4000K



Light Supply Wall Washer Trimless

Ceiling Recessed Trimless Fixed Wall-Wash

Required Accesories

Pre-installation frame Light Supply Fixed Trimless.



08.8137.00.90



Optional Accesories

Registration tray -non electrical, place holder for non IC new construction, \varnothing 6.19"


TRAY-0007



Required Accessory: Housing for Variant .90 SKU

Light Supply Housing for New construction. CCEA Chicago Plenum. Housing includes LED driver 830mA, ELV Phase Cut, 120-277V

08.8593.00.90



1 male, 1 female hanger bar Extendable from 14" to 24" centers. Qty required for housing is 2. Part number listed below is a Set of 2

08.1201.00.UL

