

## OFFSET BOARD 120 GSM – SUPERTACK – KRAFT 85 GSM

Issue: 01/032014  
Last modification:09/10/2020  
Revision: 1  
page 1/1

### GENERAL PRODUCT CHARACTERISTICS

Total weight	228 gsm ± 5%	ISO 536
Total caliper	240 µm ± 6%	ISO 534

### FACE

White uncoated board, woodfree

Substance	120 gsm ± 5	ISO 536
Caliper	138 µm ± 6	ISO 534

### ADHESIVE

Water emulsion acrylic based Supertack type, high initial tack and strong permanent bond for general use. Recommended on a wide variety of substrates, including paper, board, glass, steel

Peel adhesion	16.5/inch ± 2	FINAT1
Shear test	4h ± 2	FINAT8
Quick stick	14.4 N/inch ± 4	FINAT9
Min. application temp.	+5°C /+40°C	
Service temp. Range	-20°C/+90°C	

### BACKING

One-side coated white kraft, solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

### SAFETY REGULATIONS

- The self-adhesive product meets the European Standard EN71-3:2018 "Safety of Toys" - Migration of certain elements
- The adhesive coating meets the FDA 21 CFR 175.105 Adhesives

### APPLICATIONS

Identification labels, postcards and promotional tags, any applications where high stiffness and thickness are required.

Trials are recommended, by the purchaser, on the intended substrates, prior to use, for product suitability.

### PRINTABILITY

Face: excellent printing results by all common print processes  
Backing: good printing results by all common print processes, in one or more colors.

### ON REQUEST

- Splits on the release paper, standard spacing 38mm or customized.
- Material certified Forest Stewardship Council® FSC-C107414

### SHELF LIFE AND USE

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hrs to ambient conditions