

EUROLUB HLP 10

Category: HLP Hydraulic Fluids

**Product Features:
application:** The HLP hydraulic oils is based on paraffinic base oil and modern additive technology. Effective zinc containing components guarantee optimal lubrication and long term protection against oxidation. During the process fine filtration is possible without the risk of losing valuable ingredients.

Recommendations:

ISO 11158	AIST 126 + 127
ASTM D6158	SAE MS 1004
JCMAS P041 HK	GM LS 2

Delivery:

Art.-Nr. 500020	20 Liter	plastic-canister
Art.-Nr. 500060	60 Liter	hobbock
Art.-Nr. 500208	208 Liter	Drum
Art.-Nr. 500100	Container	800 – 3.000 Liter per destination

Technical Data:

Data	Unit	Method	EUROLUB HLP 10
Density at 15°C	kg/L	ASTM D 4052	0,854
Viscosity at 40°C	cSt	ASTM D 445	9,7
Viscosity at 100°C	cSt	ASTM D 445	2,7
Viscosityindex (VI)		ASTM D 2270	98
Flash point (COC)	°C	ASTM D 92	170
Pourpoint	°C	ASTM D 6892	-33

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.