

EUROLUB GEAR SYNT 75W/90

Description/Applications:	<p>This gear oil is a lubricating oil for mechanical transmissions, formulated with high quality special refined and base oils and special EP-additives to obtain the following properties:</p> <ul style="list-style-type: none"> - excellent resistance against oxidation - a very high activity against wear, corrosion and foam - a low pour point - very good EP-properties - fuel economy
----------------------------------	--

Can be used with:	<p>API GL-5 MIL-L-2105 D ZF TE-ML 07A / 17B</p>
--------------------------	---

Delivery:	<table> <tr> <td>Art.-Nr. 374020</td> <td>20 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 374060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 374208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 374100</td> <td>1000 Liter</td> <td>IBC</td> </tr> </table>	Art.-Nr. 374020	20 Liter	can	Art.-Nr. 374060	60 Liter	hobbock	Art.-Nr. 374208	208 Liter	drum	Art.-Nr. 374100	1000 Liter	IBC
Art.-Nr. 374020	20 Liter	can											
Art.-Nr. 374060	60 Liter	hobbock											
Art.-Nr. 374208	208 Liter	drum											
Art.-Nr. 374100	1000 Liter	IBC											

Technical Data:			
Data	Unit	Method	EUROLUB GEAR SYNT 75W/90
Density at 15°C	kg/L	ASTM D 4052	0,873
Viscosity at 40°C	cSt	ASTM D 445	87,9
Viscosity at 100°C	cSt	ASTM D 445	15,2
Viscosityindex (VI)		ASTM D 2270	184
Flash point (COC)	°C	ASTM D 92	200
Pourpoint	°C	ASTM D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 D-85386 Eching bei München Tel. 0049/8165 / 95 91 – 0, Fax 0049/8165 / 95 91 - 20 www.eurolub.de , info@eurolub.de	date: 23.01.2018, made: 23.01.2018
	reference: NSA1717, 260315
	name: GEAR SYNT 75W-90 PDS_english_374xxx
	page 1 of 1