

EUROLUB Gear EP-DB 85W/140

Description / Applications:	Gear EP-DB 85W/140 is for very highly loaded hypoid geared drive axles as well as cone and spur gears, steering gear and non-synchronized transmissions in motor vehicles and working machines aligned (according to the manufacturer's instructions!).
------------------------------------	---

Can be used with:	API GL-5
--------------------------	----------

Delivery:	Art.-Nr. 364020	20 Liter	can
	Art.-Nr. 364060	60 Liter	hobbock
	Art.-Nr. 364208	208 Liter	drum
	Art.-Nr. 364100	1000 Liter	IBC

Technical Data:			
Data	Unit	Method	EUROLUB Gear EP-DB 85W/140
Density at 15°C	kg/L	ASTM D 4052	0,903
Viscosity at 40°C	cSt	ASTM D 445	357
Viscosity at 100°C	cSt	ASTM D 445	25,7
Viscosityindex (VI)		ASTM D 2270	95
Flash point (COC)	°C	ASTM D 92	224
Pourpoint	°C	ASTM D 6892	-15

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.