

## EUROLUB Gear Fluide CVT

<b>Description / Applications:</b>	Gear Fluide CVT is designed for application in continuously variable automatic gear boxes. The so called CVTF's. Pay attention to user's manual! Color: yellow
------------------------------------	--

<b>Can be used with:</b>	MB 236.20 Mini Cooper EZL799 / EZL799A Toyota CVTF TC/FE Daihatsu Amix CVTF DC/DFC/DFE Ford WSS-M2C928-A Honda HMMF (without starting clutch) HCF2 Mitsubishi SP-III (only CVT)/CVTF-J1/J4/J4+ Subaru ECVT/iCVT/iCVT FG/NS-2 Subaru Lineartronic High Torque (HT) CVTF Subaru Lineartronic chain CVTF/CVTF II Suzuki CVTF TC/3320/NS-2/Green 1/Green 2/Green 1V Hyundai/Kia CVT-J1/ SPIII (CVT model) Chrysler/Dodge/Jeep NS-2/Mopar CVTF+4	VW G-052-180 / G-052-516 GM DEX-CVT Nissan NS-1/NS-2/NS-3 Mazda JWS 3320
--------------------------	---	---

<b>Delivery:</b>	Art.-Nr. 368001	12 x 1 Liter	bottle
	Art.-Nr. 368020	20 Liter	can
	Art.-Nr. 368060	60 Liter	hobbock
	Art.-Nr. 368208	208 Liter	drum
	Art.-Nr. 368100	1000 Liter	IBC

### Technical Data:

Data	Unit	Method	EUROLUB Gear Fluide CVT
Density at 15°C	kg/L	ASTM D 4052	0,845
Viscosity at 40°C	cSt	ASTM D 445	35,4
Viscosity at 100°C	cSt	ASTM D 445	7,3
Viscosityindex (VI)		ASTM D 2270	177
Flash point (COC)	°C	ASTM D 92	214
Pourpoint	°C	ASTM D 6892	-48

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	Druckdatum: 01.02.2018, erstellt am 31.01.2018
	Referenz: STD3302, 24.02.2017
	Name: Gear Fluide CVT PDS_EN
	Seite 1 von 1