

EUROLUB GEAR TRANS M 75W/90

| | |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description/Applications: | <p>Lightrun gear oil for longer intervals according to manufacturer's instructions.</p> <p>The full performance is only achieved unmixed.</p> <p>Optimal gear lubrication over a wide temperature range, even at very high or low outside temperatures.</p> <p>Good protection of bearings and gears in heavy use at high loads.</p> |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| | |
|--------------------------|----------------------------------------------------------------------------------|
| Can be used with: | <p>API GL-4 MB 235.11 MAN 341 Typ Z2/E1 ZF TE-ML 16A/17A/19A/19C</p> |
|--------------------------|----------------------------------------------------------------------------------|

| | |
|------------------|--------------------------------------------------------------------------------------------------------------------------|
| Delivery: | <p>Art.-Nr. 348020 20 Liter plastic canister Art.-Nr. 348060 60 Liter hobbock Art.-Nr. 348208 208 Liter drum</p> |
|------------------|--------------------------------------------------------------------------------------------------------------------------|

| Technical Data: | | | |
|------------------------|--------------------|---------------|--------------------------------------------|
| Data | Unit | Method | EUROLUB GEAR TRANS M 75W/90 |
| Density at 15°C | kg/L | DIN 51 757 | 0,891 |
| Viscosity at 40°C | mm ² /s | DIN 51 562-1 | 116,7 |
| Viscosity at 100°C | mm ² /s | DIN 51 562-1 | 18,3 |
| Viskosity Index (VI) | | DIN ISO 2909 | 171 |
| Flash point (COC) | °C | DIN ISO 2592 | 182 |
| Pourpoint | °C | DIN ISO 3016 | -42 |

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

| | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.com , info@eurolub.com | print 26.11.2018, made 26.11.2018 |
| | Referenz: NSA1713, 170418 |
| | Name: GEAR TRANS M 75W-90 PDS_english_348xxx |
| | Seite 1 von 1 |