

EUROLUB SYNT M 5W/40

Description / Applications:	<p>An extreme modern, universal motor oil based on special selected base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:</p> <ul style="list-style-type: none"> - a high and very stable viscosity index - a high resistance against shearing - a fast cold start - a very strong resistance against oxidation <p>An universal, special composed motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.</p>		
Can be used with:	<p>ACEA A3 / B4 API SN / CF VW 502.00 / 505.00 / 501.01 MB 229.5 / 229.3 BMW Longlife-01 Porsche A40 Renault RN0700 / RN0710 GM-LL-B-025 PSA B71 2296</p>		
Delivery:	<p>Art.-Nr. 395001 Art.-Nr. 395005 Art.-Nr. 395020 Art.-Nr. 395060 Art.-Nr. 395208 Art.-Nr. 395100</p>	<p>12 x 1 Liter 4 x 5 Liter 20 Liter 60 Liter 208 Liter 1000 Liter</p>	<p>bottle can can hobbock drum IBC</p>

Technical Data:

Data	Unit	Method	EUROLUB SYNT M 5W/40
Density at 15°C	kg/L	ASTM D 4052	0,856
Viscosity at 40°C	cSt	ASTM D 445	86,30
Viscosity at 100°C	cSt	ASTM D 445	14,00
Viscosityindex (VI)		ASTM D 2270	166
Flash point (COC)	°C	ASTM D 92	>200
Pourpoint	°C	ASTM D 6892	-41

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.