

EUROLUB GEAR FLUIDE ATF-A

Description/Applications:	It can be applied in automatic transmissions and torque converters as well as power steering. Excellent oxidation stability and viscosity-temperature behaviour, effective wear protection due to EP-Additives as well as excellent lubricating properties and a very low pour point characterize the product.
----------------------------------	--

Can be used with:	ATF Type A Suffix A MB 236.2 Allison C-4
--------------------------	--

Delivery:	Art.-Nr. 372020	20 Liter	canister
	Art.-Nr. 372060	60 Liter	hobbock
	Art.-Nr. 372208	208 Liter	drum
	Art.-Nr. 372100	Container	IBC 1.000L

Technical Data:

Data	Unit	Method	EUROLUB GEAR FLUIDE ATF-A
Density at 15°C	kg/L	ASTM D 4052	0,866
Viscosity at 40°C	cSt	ASTM D 445	43,2
Viscosity at 100°C	cSt	ASTM D 445	8,25
Viscosityindex (VI)		ASTM D 2270	168
Flash point (COC)	°C	ASTM D 92	198
Pourpoint	°C	ASTM D 6892	-45

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.