

## EUROLUB Gear Uni HC 80W/90

<b>Description / Applications:</b>	Gear UNI HC 80W/90 is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.
------------------------------------	---

<b>Can be used with:</b>	API GL-3 / GL-4 / GL-5 / MT-1 MIL-L-2105 / MIL-PRF-2105 E, SAE J 2360 MB 235.0 MAN 341 Typ Z2 MAN 342 Typ M2 Scania STO 1:0 Mack GO-J DAF Iveco ZF TE-ML 02B, 04G, 05A, 07A, 12L, 12M, ZF TE-ML 16B, 16C, 17H, 19B, 21A
--------------------------	---

<b>Delivery:</b>	Art.-Nr. 367020	20 Liter	can
	Art.-Nr. 367060	60 Liter	hobbock
	Art.-Nr. 367208	208 Liter	drum
	Art.-Nr. 367100	1000 Liter	IBC

<b>Technical Data:</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>EUROLUB Gear Uni HC 80W/90</b>
Density at 15°C	kg/L	ASTM D 4052	0,900
Viscosity at 40°C	cSt	ASTM D 445	146
Viscosity at 100°C	cSt	ASTM D 445	15,2
Viscosityindex (VI)		ASTM D 2270	105
Flash point (COC)	°C	ASTM D 92	200
Pourpoint	°C	ASTM D 6892	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	Druckdatum: 01.02.2018, erstellt am 01.02.2018
	Referenz: NSA1613, 29.11.2017
	Name: Gear Uni HC 80W-90 PDS_EN
	Seite 1 von 1