

EUROLUB DOPPELKUPPLUNGSFLUID (DKG)

Description/Applications:	Eurolub Doppelkupplungsfluid (DKG) is developed to fulfill the highest demands of modern high tech dual clutch transmissions and is particularly suitable for transmissions where clutch, synchronizer, gear set and hydraulic control system operate with the same fluid. Color: yellow as oil
----------------------------------	--

Can be used with:	VW G-052-529 / VW G-052-182 BMW Ford WSS-M2C-936-A MB 236.21 / MB 236.25 Mitsubishi Dia-Queen SSTF-1 PSA Porsche Volvo 1161838 / 1161839
--------------------------	---

Delivery:	Art.-Nr. 545001	12 x 1 Liter	bottle
	Art.-Nr. 545020	20 Liter	can
	Art.-Nr. 545060	60 Liter	hobbock
	Art.-Nr. 545208	208 Liter	drum
	Art.-Nr. 545100	Container	IBC

Technical Data:			
Data	Unit	Method	EUROLUB DKF (DKG)
Density at 15°C	kg/L	D 4052	0,854
Viscosity at 40°C	cSt	D 445	34,0
Viscosity at 100°C	cSt	D 445	7,0
Viscosityindex (VI)		D 2270	173
Flash point (COC)	°C	D 92	201
Pourpoint	°C	D 6892	-48

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49(0)8165 / 95 91 - 0, Fax +49(0)8165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	Druckdatum: 31.01.2018, erstellt am 31.01.2018
	Referenz: STD3303, 08.07.2017
	Name: Doppelkupplungsfluid DKG PDS_GB
	Seite 1 von 1