

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2015

Version number 13

Revision: 13.03.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *EUROMIX 2-TAKT Gerätebenzin*
- **Article number:** 32583
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture fuel**
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
EUROLUB GmbH
Freisinger Strasse 25-27

85386 Eching
- **Further information obtainable from:**
Telefon-Nr. 08165/9591-0
www.eurolub.com
- **1.4 Emergency telephone number:** 08165/9591-0 (während der Geschäftszeiten)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 1 H224 Extremely flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
Benzin
- **Hazard statements**
H224 Extremely flammable liquid and vapour.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2015

Version number 13

Revision: 13.03.2015

Trade name: EUROMIX 2-TAKT Gerätebenzin

(Contd. of page 1)

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P301+P310 IF SWALLOWED: Immediately call a doctor.
- P331 Do NOT induce vomiting.
- P370+P378 In case of fire: Use for extinction: CO₂, sand, extinguishing powder.
- P403+P235 Store in a well-ventilated place. Keep cool.

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients**· 3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 86290-81-5 EINECS: 289-220-8 Reg.nr.: 01-2119471335-39	Benzin Flam. Liq. 1, H224; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
---	--	---------

· Additional information:

For the wording of the listed risk phrases refer to section 16.
conform to the Swedish standard SS 155461: benzene (CAS 71-43-3) < 0,1 Vol.%, hexane (CAS 110-54-3) < 0,5 Vol.%, aromatic compounds < 0,5 Vol.%, olefins < 0,5%.

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:**
Aspiration hazard!
Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media**

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Builds slippery and with water smeary coatings

The vapors of this product are heavier than air. They could concentrate on the floor, in caverns, channels and basements and inflame again.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2015

Version number 13

Revision: 13.03.2015

Trade name: **EUROMIX 2-TAKT Gerätebenzin**

(Contd. of page 2)

- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Use only in well ventilated areas.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Follow TRGS 501
Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** LGK 3 A
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2015

Version number 13

Revision: 13.03.2015

Trade name: **EUROMIX 2-TAKT Gerätebenzin**

(Contd. of page 3)

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **DNELs**

86290-81-5 Benzin

Inhalative	DNEL acute systemic effect	1300 mg/m ³ (Workers) 1200 mg/m ³ (General population)
	DNEL acute, local effect	1100 mg/m ³ (Workers) 640 mg/m ³ (General population)
	DNEL longterm. local effect	840 mg/m ³ (Workers) 180 mg/m ³ (General population)

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

Filter A/P2
Use suitable respiratory protective device in case of insufficient ventilation.

- **Protection of hands:**



Protective gloves

- **Material of gloves** Nitrile rubber, NBR

- **Penetration time of glove material**

longterm contact:
NBR: thickness:0,425 mm; break trough: 240 - 480 min.
shortterm contact:
NBR: thickness 0,12; break trough: 10 - 30 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	Green
Odour:	Characteristic

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2015

Version number 13

Revision: 13.03.2015

Trade name: EUROMIX 2-TAKT Gerätebenzin

(Contd. of page 4)

· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	< 35 °C (DIN 51751)
· Flash point:	< -18 °C (DIN ISO 2592)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.4 Vol %
Upper:	7.6 Vol %
· Vapour pressure:	Not determined.
· Density:	0,685 g/cm ³ 15 °C (DIN 51757)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	0.92 log POW (OECD 107)
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	
· Solvent content:	
Organic solvents:	0.0 %
VOC (EC)	97.50 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** Avoid naked flames and other ignition sources.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

86290-81-5 Benzin

Oral	LD50 > 5000 mg/kg (rat) (OECD 401)
------	------------------------------------

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2015

Version number 13

Revision: 13.03.2015

Trade name: EUROMIX 2-TAKT Gerätebenzin

(Contd. of page 5)

Dermal	LD50	> 2000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50	>5.61 mg/l (rat) (OECD 403)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **Sensitisation:** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
- **Toxicokinetics, metabolism and distribution** No further relevant information available.
- **Repeated dose toxicity** No further relevant information available.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
No further relevant information available.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

EC50	> 100 mg/l (algae) (OECD 201)
	> 100 mg/l (daphnia) (OECD 202)
	> 100 mg/l (fish) (OECD 203)
NOEC	100 mg/l (algae) (OECD 201)
	100 mg/l (daphnia) (OECD 202)
	100 mg/l (fish) (OECD 203)

86290-81-5 Benzin

EC50	15.4 mg/l (microorganisms) (QSAR, 40 h)
	3.7 mg/l (algae) (OECD 201)
	4.5 mg/l (daphnia) (OECD 202)
	8.2 mg/l (fish) (OECD 203)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential**
Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.
- **12.4 Mobility in soil**
The product consists mainly of slightly evaporating volatile organic compounds (VOC). The product is not soluble in water and will be disposed and evaporated on the water surface.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2015

Version number 13

Revision: 13.03.2015

Trade name: EUROMIX 2-TAKT Gerätebenzin

(Contd. of page 6)

· **European waste catalogue**

13 07 02* petrol

15 01 02 plastic packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**· **14.1 UN-Number**· **ADR, IMDG, IATA**

UN1203

· **14.2 UN proper shipping name**· **ADR**

1203 GASOLINE

· **IMDG, IATA**

GASOLINE

· **14.3 Transport hazard class(es)**· **ADR, IMDG, IATA**· **Class**

3 Flammable liquids.

· **Label**

3

· **14.4 Packing group**· **ADR, IMDG, IATA**

II

· **14.5 Environmental hazards:**· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Danger code (Kemler):**

33

· **EMS Number:**

F-E,S-E

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category**

2

· **Tunnel restriction code**

D/E

· **UN "Model Regulation":**

UN1203, GASOLINE, 3, II

SECTION 15: Regulatory information· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **National regulations:**· **Information about limitation of use:** Employment restrictions concerning juveniles must be observed.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2015

Version number 13

Revision: 13.03.2015

Trade name: EUROMIX 2-TAKT Gerätebenzin

(Contd. of page 7)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H224 Extremely flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 1: Flammable liquids, Hazard Category 1

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

GB