

EUROLUB SCHNEIDÖL MS2

Properties:	<p>Cutting oil MS2 is an EP multipurpose cutting oil. It has the following properties:</p> <ul style="list-style-type: none"> • Chlorine • Not water-miscible
--------------------	---

Application:	<p>Cutting oil MS2 is suitable for machining steel and non-ferrous metals, such as turning and gear cutting. The product can also be used for processing tough steels, e.g. Ball bearing steels, heat resistant steels and alloys of very high strength can be used. The selected chemical EP additives prevent welding between the chip and the cutting edge.</p>
---------------------	--

Delivery:	Art.-Nr. 620020	20 Liter	canister
	Art.-Nr. 620060	60 Liter	hobbock
	Art.-Nr. 620208	208 Liter	drum

Technical Data			
Data	Unit	Method	EUROLUB SCHNEIDÖL MS2
Density	kg/L		0,876
Viscosity at 40°C	mm ² /s		32,0
Flashpoint	°C		>200
Copper corrosion			Note 1

The data given may be subject to change. Observe the operating instructions of the manufacturer. We reserve the right to make data changes due to the further development of product and production. This information is intended to describe the product and therefore does not have the meaning to assure certain properties. A liability can not be derived from this.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 05.12.2018, made 05.12.2018
	Referenz: x-cut
	Name: SCHNEIDÖL MS2 PDS_english_620xxx
	Seite 1 von 1