

EUROLUB GEAR EP 85W/90

Description/Applications:	Gear EP 85W/90 are multipurpose EP gear oils, their universal use, the supply of gearboxes (with and without synchronization), transfer gear, steering gears and different normal traffic driving axles - especially car transaxle systems - is possible. Can not be used when hypoid gear oils according to MIL-L-2105 B / C or API GL-5 mandatory.
----------------------------------	--

Can be used with:	API GL-4
--------------------------	----------

Delivery:	Art.-Nr. 362020	20 Liter	plastic canister
	Art.-Nr. 362060	60 Liter	hobbock
	Art.-Nr. 362208	208 Liter	drum
	Art.-Nr. 362100	800 – 3.000 Liter	Container per destination

Technical Data:			
Data	Unit	Method	EUROLUB Gear EP 85W/90
Density at 15°C	Kg/l	DIN 51 757	0,890
Viscosity at 40°C	mm ² /s	DIN 51 562	177
Viscosity at 100°C	mm ² /s	DIN 51 562	16,0
Flash point (COC)	°C	DIN ISO 2592	>210
Pourpoint	°C	DIN ISO 3016	<-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.