

EUROLUB NIROSTOL 1 – Sprühöl hell

Product features / Application:	<p>NIROSTOL 1 is a low-viscosity and solvent-free corrosion protection oil.</p> <p>APPLICATION: NIROSTOL 1 is used for preserving longer-stored workpieces of all kinds, such as machine parts, tools, hardware and sheet metal parts. The application of NIROSTOL 1 can be done by dipping and brushing. The adhering oil film does not need to be removed before putting the parts into operation. The oil film can be easily removed with petroleum or other solvents at any time. The product contains no harmful substances. With NIROSTOL 1, a protection period of about 4 to 6 months can be achieved when stored in a closed room.</p> <p>PROPERTIES:</p> <ul style="list-style-type: none"> • Sprayable • glow residue-free • Forms homogeneous oil protection films • Effective corrosion protection
--	---

Delivery:	Art.-Nr. 541020	20 Liter	plastic-can
	Art.-Nr. 541060	60 Liter	hobbock
	Art.-Nr. 541208	208 Liter	drum

Technical Data:			
Data:	Unit:	Method:	EUROLUB Nirostol 1
Density at 15°C	g/cm ³	DIN 51 757	0,85
Viskosity at 40°C	mm ² /s	DIN 51 562	6,35
Flash point COC	°C	DIN ISO 51376	> 160
Pour point	°C	DIN ISO 3016	< -15

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 19.12.2018, made 19.12.2018
	Referenz: xtbev/0818
	name: NIROSTOL 1 PDS_english_541xxx
	Seite 1 von 1