

## EUROLUB Multitec FO SAE 0W/30

<b>Description / Applications:</b>	This fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters. Very suitable for Ford engines where the manufacturer prescribes a product that meets the specification Ford WSS-M2C950-A with the viscosity SAE 0W30.
------------------------------------	---

<b>Can be used with:</b>	ACEA C2 Ford WSS-M2C950-A Jaguar Land Rover STJLR.03.5007
--------------------------	---

<b>Delivery:</b>	Art.-Nr. 319001	12 x 1 Liter	bottle
	Art.-Nr. 319005	4 x 5 Liter	can
	Art.-Nr. 319020	20 Liter	can
	Art.-Nr. 319060	60 Liter	hobbock
	Art.-Nr. 319208	208 Liter	drum
	Art.-Nr. 319100	Container	IBC

### Technical Data:

Data	Unit	Method	EUROLUB Multitec FO SAE 0W/30
Density at 15°C	kg/L	D 4052	0,845
Viscosity at 40°C	cSt	D 445	49,3
Viscosity at 100°C	cSt	D 445	10,0
Viscosityindex (VI)		D 2270	195
Flash point (COC)	°C	D 92	230
Pourpoint	°C	D 6892	-45

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.