

EUROLUB HLP-D 46

Category: HLPD Hydraulic Fluids

**Product Features:
application:** The HLPD hydraulic oils is based on paraffinic base oil and modern additive technology. Effective zinc containing components guarantee optimal lubrication and long term protection against oxidation. During the process fine filtration is possible without the risk of losing valuable ingredients. Because of the high viscosity index the lubricating effect of the oil remains unaffected even at very high temperatures. Dispersant and detergent additives provide optimal dirt-removing properties and the product is especially suitable for centrally supplied machines.

Recommendations:	DIN 51 524 / part 2	FZG-Test A8, 3/90 load stage: >12
	ISO VG 46	VW steel corrosion test P-VW 1425
	MAN N 698	

Delivery:	Art.-Nr. 51102020 Liter	plastic-canister
	Art.-Nr. 51106060 Liter	hobbock
	Art.-Nr. 511208208 Liter	Drum
	Art.-Nr. 511100 Container	800 – 3.000 Liter per destination

Technical Data:

Data	Unit	Method	EUROLUB HLP-D 46
Density at 15°C	kg/L	ASTM D 4052	0,866
Viscosity at 40°C	cSt	ASTM D 445	44,8
Viscosity at 100°C	cSt	ASTM D 445	6,8
Viscosityindex (VI)		ASTM D 2270	113
Flash point (COC)	°C	ASTM D 92	230
Pourpoint	°C	ASTM D 6892	-27

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.de , info@eurolub.de	print: 06.06.2017, made 06.06.2017
	Referenz: P150167_HLPD46
	Name: HLP-D 46 PDB_EN
	Seite 1 von 1