

EUROLUB Gear LS 80W/90

Description / Applications:	Gear LS 80W/90 has especially been developed for the perfect lubrication of so-called "Limited Slip" and "Auto-Locking" hypoid transmissions. Gear LS 80W / 90 can be used in mixed fleets for variety reduction also in all drive axles with the requirement API GL 5. The operating instructions of the vehicle and engine manufactures must be followed.
------------------------------------	---

Can be used with:	API GL-5 / LS (Limited Slip) MIL-L 2105 D ZF TE-ML 05C
--------------------------	--

Delivery:	Art.-Nr. 375020	20 Liter	can
	Art.-Nr. 375060	60 Liter	hobbock
	Art.-Nr. 375208	208 Liter	drum
	Art.-Nr. 375100	1000 Liter	IBC

Technical Data:			
Data	Unit	Method	EUROLUB Gear LS 80W/90
Density at 15°C	kg/L	ASTM D 4052	0,903
Viscosity at 40°C	cSt	ASTM D 445	150
Viscosity at 100°C	cSt	ASTM D 445	15,1
Viscosityindex (VI)		ASTM D 2270	100
Flash point (COC)	°C	ASTM D 92	210
Pourpoint	°C	ASTM D 6892	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 26.11.2018 made 26.11.2018
	Referenz: STA1905, 130418
	Name: Gear LS SAE 80W90 PDS_english_375xxx
	Seite 1 von 1