

EUROLUB GEAR TRANS SL 75W/80

Description/Applications:	<p>This gear oil is a lubricating oil for mechanical transmissions, formulated with high quality synthetic base oils and special EP-additives to obtain the following properties: - an excellent thermal stability - a very high activity against wear, corrosion and foam - a low pour point - very high quality EP-properties - good clutch-switch performance at low temperatures - long durability - fuel economy</p> <p>This gear oil is special developed for gearboxes under very heavy duty conditions together with high temperatures. This oil can also be used for extended drain intervals.</p>
----------------------------------	---

Can be used with:	<p>API GL-4 MAN 341 Typ Z4 ZF TE-ML 01L / 02L / 08 / 13 / 16K DAF Volvo 97307 Eaton Europe (extended drain) Iveco Renault</p>
--------------------------	---

Delivery:	Art.-Nr. 346020	20 Liter	canister
	Art.-Nr. 346060	60 Liter	hobbock
	Art.-Nr. 346208	208 Liter	drum
	Art.-Nr. 346100	Container	IBC 1.000L

Technical Data:

Data	Unit	Method	EUROLUB Gear Trans SL 75W-80
Density at 15°C	kg/L	ASTM D 4052	0,858
Viscosity at 40°C	cSt	ASTM D 445	65,00
Viscosity at 100°C	cSt	ASTM D 445	10,00
Viscosityindex (VI)		ASTM D 2270	155
Flash point (COC)	°C	ASTM D 92	>200
Pourpoint	°C	ASTM D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print 26.11.2018, made 26.11.2018
	Sta1802, 220818
	Name: GEAR TRANS SL 75W-80 PDS_english_346xxx
	Seite 1 von 1