PRODUCT INFORMATION



EUROLUB Supertec SAE 5W/20

Description / Applications:	Consented CAE ENV/20 is a final agricular all based on symbolic base
Description / Applications:	Supertec SAE 5W/20 is a fuel saving oil based on synthetic base
	oils specially developed for the Ford Ecoboost gasoline. This SAE
	5W/20 engine oil can also be used were an ACEA C5 or API SN
	product is recommended by car manufacturers.

Can be used with:	ACEA C5, A1/B1	
	API SN	
	Ford WSS-M2C948-B	
	Jaguar Land Rover STJLR.03.5004	

Delivery:	ArtNr. 314001	12 x 1 Liter	bottle
	ArtNr. 314020	20 Liter	can
	ArtNr. 314060	60 Liter	hobbock
	ArtNr. 314208	208 Liter	drum
	ArtNr. 314100	Container	IBC

Technical Data:				
Data	Unit	Method	EUROLUB Supertec SAE 5W/20	
Density at 15°C	kg/L	D 4052	0,851	
Viscosity at 40°C	cSt	D 445	42,6	
Viscosity at 100°C	cSt	D 445	7,85	
Viscosityindex (VI)		D 2270	157	
Flash point (COC)	°C	D 92	218	
Pourpoint	°C	D 6892	-36	

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.