

# PRODUCT INFORMATION



## EUROLUB Autolack schwarz matt

<b>Category:</b>	paint work spray
------------------	------------------

<b>Product Features:</b>	The paint work spray can be used for sports design as well for repair purposes. It is characterized by high opacity, good adhesion and quick drying.
--------------------------	--

<b>Application:</b>	Shake well, after which the ball can be heard further shake for about 2 minutes. The area to be treated must be dry and free of dust. Spray distance of about 30 cm. Only thin films spray on, avoid sun and wind. After use, turn can upside down and spray until empty valve.
---------------------	---

<b>EAN:</b>	Art.-Nr. 00017 0	400 ml	4 025377 00017 6
-------------	------------------	--------	------------------

<b>Lieferformen:</b>	Art.-Nr. 00017 0	12 x 400 ml	aerosol can
----------------------	------------------	-------------	-------------

<b>Technical Data:</b>	
<b>Chemical Base:</b>	Paint work spray on the basis of acrylic resin combination in solvents.
<b>Density:</b>	0,771 g/ml
<b>PH-value:</b>	k.A.
<b>Marking:</b>	See section 15 of the current safety data sheet
<b>General Information:</b>	Product does not contain halogenated hydrocarbons.

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Straße 25-27 85386 Eching bei München Tel. 08165 / 95 91 - 0, Fax 08165 / 95 91 - 20 <a href="http://www.eurolub.de">www.eurolub.de</a> , <a href="mailto:info@eurolub.de">info@eurolub.de</a>	Druckdatum: 12.10.2015, erstellt am 04.03.2014/hb
	Autor: MS, Referenz: xklotkatib, Januar 2006
	Name: Autolack schwarz matt 400 ml PDS_GBDS(GB)
	Seite 1 von 1