

EUROLUB Multitec SAE 5W/30

Description / Applications:	This fuel economy motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below. This motor oil is specially developed for those cars, that ask for motor oils that fulfill the recent requirements of the OEM's. This oil is fully backwards compatible with Ford M2C 913-A, B and C.
------------------------------------	--

Can be used with:	ACEA A5/B5 A1/B1 API SL/CF Ford WSS-M2C913-D Renault RN0700 Jaguar Land Rover STJLR.03.5003
--------------------------	---

Delivery:	Art.-Nr. 214001	12 x 1 Liter	bottle
	Art.-Nr. 214005	4 x 5 Liter	can
	Art.-Nr. 214020	20 Liter	can
	Art.-Nr. 214060	60 Liter	hobbock
	Art.-Nr. 214208	208 Liter	drum
	Art.-Nr. 214100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB Multitec SAE 5W/30
Density at 15°C	kg/L	D 4052	0,845
Viscosity at 40°C	cSt	D 445	54,5
Viscosity at 100°C	cSt	D 445	9,9
Viscosityindex (VI)		D 2270	170
Flash point (COC)	°C	D 92	220
Pourpoint	°C	D 6892	-39

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.