

EUROLUB AdBlue[®]

For exhaust aftertreatment of automotive diesel engines with SCR-technology.

Discription: Application:	High-purity urea solution for SCR exhaust aftertreatment / AUS 32 acc. ISO 22241. Application: Do not fill in the fuel tank or other liquid containers of the vehicle, but only in the designated and separate AdBlue [®] tank! AdBlue [®] is a registered trademark of the Association of the Automotive Industrie e.V. (VDA).
Product feature: Storage:	Recommended storage temperature between 0 ° C and + 30 ° C. Avoid direct sunlight. If not used, seal AdBlue [®] containers airtight. AdBlue [®] can freeze at -11 ° C. Therefore, it is important that you use a storage location where the temperature can not drop below this level. If AdBlue [®] is frozen, it can be reused after thawing as it returns to its original state. If the instructions for storage are followed correctly, AdBlue can be stored for up to one year.
Can be used with:	AUS 32 gem. ISO 22241

Delivery:	Art.-Nr. 845005 4 x 5 Liter can VPE palett = 96 x 5 Liter Art.-Nr. 845010 10 Liter can VPE palett = 60 x 10 Liter Art.-Nr. 845020 20 Liter can VPE palett = 28 x 20 Liter Art.-Nr. 845060 60 Liter drum VPE palett = 16 x 60 Liter Art.-Nr. 845208 208 Liter drum VPE palett 2 x 208 Liter Art.-Nr. 845100 1.000 IBC
------------------	---

The specified data can make changes. Observe the operating instructions of the manufacturer. Conditional data changes reserved. This information is intended to describe the product and is not intended to assert certain characteristics. A liability can not be derived from this.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 07.01.2019, made 07.01.2019
	Referenz: hoAdBlue, 081015
	Name: ADBLUE PDS_english_845xxx
	Seite 1 von 1