

## EUROLUB Cleantec DX 1G2 SAE 5W/30

<b>Description/Applications:</b>	Cleantec DX 1G2 SAE 5W/30 is a modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balance choice of advanced additives. A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1™ Gen 2. Cleantec DX 1G2 SAE 5W/30 minimizes the LSPI (Low Speed Pre-Ignition) effect.
----------------------------------	---

<b>Can be used with:</b>	API SN / API SN Plus ILSAC GF-5 GM dexos1™ Gen 2 Chrysler MS 6395 Ford M2C946-A
--------------------------	---

<b>Delivery:</b>	Art.-Nr. 385001	12 x 1 Liter	bottle
	Art.-Nr. 385005	4 x 5 Liter	can
	Art.-Nr. 385020	20 Liter	can
	Art.-Nr. 385060	60 Liter	hobbock
	Art.-Nr. 385208	208 Liter	drum
	Art.-Nr. 385100	Container	IBC

<b>Technical Data:</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>EUROLUB Cleantec DX 1G2 5W/30</b>
Density at 15°C	kg/L	D 4052	0,851
Viscosity at 40°C	cSt	D 445	61,8
Viscosity at 100°C	cSt	D 445	11,3
Viscosityindex (VI)		D 2270	179
Flash point (COC)	°C	D 92	224
Pourpoint	°C	D 6892	-39

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49(0)8165 / 95 91 - 0, Fax +49(0)8165 / 95 91 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	Print: 26.11.2018, made: 26.11.2018
	Referenz: NSA0607, 070518
	Name: Cleantec DX 1G2 SAE 5W-30 PDS_english_385xxx
	Seite 1 von 1