

## EUROLUB Multicargo 10W/40

<b>Description/Applications:</b>	MULTICARGO 10W/40 is a Ultra-High-Performance-Diesel motor oil. This product has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for Euro 4 and Euro 5 engines without particelfilter and for the most engines with exhaustgasemission systems. The operating instructions of the vehicle and engine manufactures must be followed.
----------------------------------	---

<b>Can be used with:</b>	ACEA E4 / E7 API CI-4 MB 228.5 Volvo VDS-3 Renault VI RXD/RLD-2 Deutz IV-10 Cummins CES 20078	MAN M 3377 / 3277 Global DHD-1 MTU Type 3 Mack EO-N / EO-M plus Detroit Diesel 93K215
--------------------------	---	---

<b>Delivery:</b>	Art.-Nr. 318020	20 Liter	can
	Art.-Nr. 318060	60 Liter	hobbock
	Art.-Nr. 318208	208 Liter	drum
	Art.-Nr. 318100	Container	IBC

### Technical Data:

Data	Unit	Method	EUROLUB Multicargo 10W/40
Density at 15°C	kg/L	D 4052	0,865
Viscosity at 40°C	cSt	D 445	107
Viscosity at 100°C	cSt	D 445	14,8
Viscosityindex (VI)		D 2270	150
Flash point (COC)	°C	D 92	226
Pourpoint	°C	D 6892	-36

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.