

EUROLUB GTS 20W/50

Description/Applications:	It is a multigrade oil, which meet all requirements of spark-ignition petrol or diesel engines. The adjustable viscosities guarantee good lubrication under all operating conditions. According to some manufacturers' recommendations these oils can be used throughout the year.
----------------------------------	--

Can be used with:	API CH-4 / CF-4 / SJ ACEA A3/B3, E2 MB 228.1, MB 229.1 MAN 271 Volvo VDS CAT TO2 Allison C-4
--------------------------	--

Delivery:	Art.-Nr. 325001	12 x 1 Liter	bottle
	Art.-Nr. 325005	4 x 5 Liter	can
	Art.-Nr. 325020	20 Liter	canister
	Art.-Nr. 325060	60 Liter	hobbock
	Art.-Nr. 325208	208 Liter	drum
	Art.-Nr. 325100	Container	IBC 1.000L

Technical data:			
Data	Unit	Method	EUROLUB GTS 20W/50
Density at 15°C	kg/L	ASTM D 4052	0,887
Viscosity at 40°C	cSt	ASTM D 445	154
Viscosity at 100°C	cSt	ASTM D 445	19,0
Viscosityindex (VI)		ASTM D 2270	>120
Flash point (COC)	°C	ASTM D 92	220
Pourpoint	°C	ASTM D 6892	<-21

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 D-85386 Eching bei München Tel. 0049/8165 / 95 91 – 0, Fax 0049/8165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 26.03.2018, made 20.03.2018
	reference: evgfp2050
	name: GTS 20W-50 PDS_GB
	page 1 of 1