

EUROLUB FORMEL 2 SAE 10W/40

Description/Applications:	<p>It is designed for the lubrication of four –stroke gasoline and diesel cars, including diesel engines with direct injection. Key features include a low ash formulation and a high resistance to ageing.</p> <p>Ideal for most gasoline and diesel engines. Particularly recommended for Direct Injection diesel engines. Pay attention to users manual !!</p>
----------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Can be used with:	<p>ACEA A3/B4 API SL/CF</p>
--------------------------	---------------------------------

Delivery:	<table> <tr> <td>Art.-Nr. 237005</td> <td>4 x 5 Liter</td> <td>canister</td> </tr> <tr> <td>Art.-Nr. 237020</td> <td>20 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 237060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 237208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 237100</td> <td>1000 Liter</td> <td>IBC</td> </tr> </table>	Art.-Nr. 237005	4 x 5 Liter	canister	Art.-Nr. 237020	20 Liter	can	Art.-Nr. 237060	60 Liter	hobbock	Art.-Nr. 237208	208 Liter	drum	Art.-Nr. 237100	1000 Liter	IBC
Art.-Nr. 237005	4 x 5 Liter	canister														
Art.-Nr. 237020	20 Liter	can														
Art.-Nr. 237060	60 Liter	hobbock														
Art.-Nr. 237208	208 Liter	drum														
Art.-Nr. 237100	1000 Liter	IBC														

Technical data:			
Data	Unit	Method	EUROLUB Formel 2 10W/40
Density at 15°C	kg/L	ASTM D 4052	0,867
Viscosity at 40°C	cSt	ASTM D 445	90,4
Viscosity at 100°C	cSt	ASTM D 445	14,1
Flash point (COC)	°C	ASTM D 92	226
Pourpoint	°C	ASTM D 6892	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 D-85386 Eching - Germany Tel. 0049/8165 / 95 91 – 0, Fax 0049/8165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 22.11.2018, made: 20.11.2018
	reference: r20259 / 121017
	name: FORMEL 2 SAE 10W-40 PDS_english_237xxx
	page 1 of 1