

## EUROLUB GEAR FLUIDE 15 BM

<b>Description/Applications:</b>	Low-Viscosity ATF for maximum fuel economy potential. Adapted to the requirements of Mercedes-Benz 7-speed automatic transmissions from 06/2010. Color: blue
----------------------------------	---

<b>Can be used with:</b>	MB 236.15
--------------------------	-----------

<b>Delivery:</b>	Art.-Nr. 366001	12 x 1 Liter	bottle
	Art.-Nr. 366020	20 Liter	canister
	Art.-Nr. 366060	60 Liter	hobbock
	Art.-Nr. 366208	208 Liter	drum
	Art.-Nr. 366100	Container	IBC 1.000L

### Technical Data:

Data	Unit	Method	EUROLUB GEAR FLUIDE 15 BM
Density at 15°C	kg/L	ASTM D 4052	0,843
Viscosity at 40°C	cSt	ASTM D 445	24,3
Viscosity at 100°C	cSt	ASTM D 445	5,3
Viscosityindex (VI)		ASTM D 2270	165
Flash point (COC)	°C	ASTM D 92	200
Pourpoint	°C	ASTM D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.