

## EUROLUB Gasmotorenöl LA SAE 40

<b>Description/Applications:</b>	<p>LA SAE 40 is a gas engine oil with medium to low sulfated ash content. The good formulation protects against early ignitions, engine knocking and provides an adequate alkalinity compared to the use of slightly aggressive combustion gases.</p> <p>LA SAE 40 is used in stationary gas engines, according to the manufacturer in operation with natural gas, landfill gas and biogas for medium to heavy conditions.</p>		
<b>Can be used with:</b>	<p>API SF / CC CCMC G2/D1 MAN 3271-1 MTU 400 series MWM TR 0199-99-2105 (Ash content up to 0,5 %)</p>		
<b>Delivery:</b>	Art.-Nr. 307020	20 Liter	plastic canister
	Art.-Nr. 307060	60 Liter	hobbock
	Art.-Nr. 307208	208 Liter	Drum
	Art.-Nr. 307100	Container	800 – 3.000 Liter per destination

<b>Technical Data:</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>EUROLUB Gasmotorenöl LA SAE 40</b>
Density at 15°C	kg/L	D 4052	0,893
Viscosity at 40°C	mm <sup>2</sup> /s	D 445	143,0
Viscosity at 100°C	mm <sup>2</sup> /s	D 445	14,7
Pourpoint	°C	D 97	-21
base number (TBN)	mgKOH/g	D 2896	5,1
Sulfate ash content	%	D 874	0,45

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	print: 21.11.2018, made 20.11.2018
	Referenz: STA0403
	Name: Gasmotorenöl LA SAE 40 PDS_english_307xxx
	Seite 1 von 1