

EUROLUB TURBO STAR 15W/40

Description/Applications:	Turbo Star 15W/40 is a multigrade motor oil for diesel and gasoline engines. The viscosity range SAE 15W/40 ensures throughout the year reliable cold starting and high temperature resistance even under extreme conditions. Shear-stable materials ensure compliance with the viscosity range SAE 15W/40. The combination of selected base oils and additives effected very good wear protection and excellent engine cleanliness, the formation of black sludge is prevented.		
Can be used with:	API CF-4/SJ MB 228.1 MAN 271 Volvo VDS		
Delivery:	Art.-Nr. 340001	12 x 1 Liter	plastic bottle
	Art.-Nr. 340005	4 x 5 Liter	plastic canister
	Art.-Nr. 340020	20 Liter	plastic canister
	Art.-Nr. 340060	60 Liter	hobbock
	Art.-Nr. 340208	208 Liter	Drum
	Art.-Nr. 340100	IBC - Container	

Technical Data:			
Data:	Unit:	Method:	EUROLUB Turbo Star 15W/40
Density at 15°C	kg/L	ASTM D 4052	0,863
Viscosity at 40°C	cSt	ASTM D 445	103
Viscosity at 100°C	cSt	ASTM D 445	15,3
Viscosityindex (VI)		ASTM D 2270	150
Flash point (COC)	°C	ASTM D 92	220
Pourpoint	°C	ASTM D 6892	-33

The data provided are subject to change. Operating rules of the manufacturer.Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.de , info@eurolub.de	Druckdatum: 28.11.2018, erstellt am 28.11.2018
	Referenz: 150061, 07/2018
	Name: TURBO STAR 15W-40 PDS_english_340xxx
	Seite 1 von 1