

## EUROLUB MEHRBEREICHSHYDRAULIKÖL 10W/30

<b>Description/Applications:</b>	It is a high quality hydraulic oil with excellent viscosity-temperature behavior for use in high pressure hydraulic systems operating in areas with changing temperatures. High quality base oils ensure excellent aging resistance and corrosion protection effect in combination with oxidation and corrosion inhibitors. EP additives minimize wear. HVLP is neutral with respect to seals and hoses.
----------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>Can be used with:</b>	DIN 51 524 / Teil 3 HVLP ISO-VG 32 - 68
--------------------------	--------------------------------------------

<b>Delivery:</b>	Art.-Nr. 320020	20 Liter	canister
	Art.-Nr. 320060	60 Liter	hobbock
	Art.-Nr. 320208	208 Liter	drum
	Art.-Nr. 320100	Container	IBC 1.000L

### Technical Data:

Data	Unit	Method	EUROLUB Mehrbereichsh. SAE 10W-30
Density at 15°C	kg/L	D 4052	0,862
Viscosity at 40°C	cSt	D 445	43,1
Viscosity at 100°C	cSt	D 445	7,9
Viscosityindex (VI)		D 2270	155
Flash point (COC)	°C	D 92	220
Pourpoint	°C	D 6892	-39

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.