

PRODUCT INFORMATION



EUROLUB Kupferpaste

Category: special Lubricant

Product Features: Prevents galling, seizing and rusting of bolts, threaded fasteners, bolts und valves. Due to the high temperature resistance up to 1100 ° C Suitable for exhaust systems, spark plug threads, nuts, gaskets to cylinder head and carburetor. Resistant to water, acids and alkalis.

Application: The area to be treated should be dry and free of dust. Shake can well before use and apply copper grease evenly.

EAN: Art.Nr. 00438 3 400 ml 4025377004389

Delivery: Art.Nr. 00438 3 12 x 400 ml Aerosol can

Technical Data:

Chemical Basis:	Preparation of (natural) greases, synthetic. Hydrocarbons and copper powder in a solvent.
Density:	0,7 g/cm ³
PH-Value:	k.A.
Marking:	See section 15 of the current EC safety data sheet.
General Informations:	Product does not contain halogenated hydrocarbons.

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 - 0, Fax 08165 / 95 91 - 20 www.eurolub.de , info@eurolub.de	Druckdatum: 12.10.2015, erstellt am 19.02.2014/hb
	Autor: GD
	Name: Kupferpaste 400 ml PDS_GB
	Seite 1 von 1