

EUROLUB Gear Fluide AS

Description / Applications:	Gear Fluide AS may be used for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications. It is recommended to follow the instructions of the manufacturer.
------------------------------------	--

Can be used with:	MB 236.1 / 236.6 / 236.7 / 236.8 / 236.9 / 236.10 BMW 7045E / 8072B Chrysler ATF+3 / ATF+4 Toyota ATF T-III / T-IV / D-II / WS Nissan Matic Fluid C/D/J/K Honda ATF-Z1 (except in CVT) Mazda ATF M-V Hyundai/Kia SP-II / SP-III Suzuki ATF 3314 Subaru ATF/ATF 5AT/ATF HP/Dexron II GM Dexron IID / IIE / IIIG / IIIH, TASA Ford Mercon M2C 138 CJ / 166H / 922A1 / 924A Aisin Warner JWS 3309/3324 Isuzu Besco ATF II / III Allison C4 / TES-228 JASO M 315-2013 Type 1A VAG G-055-025 Volvo 1161540 ZF TE-ML 09/11A/11B
--------------------------	---

Delivery:	Art.-Nr. 371001	12 x 1 Liter	bottle
	Art.-Nr. 371020	20 Liter	can
	Art.-Nr. 371060	60 Liter	hobbock
	Art.-Nr. 371208	208 Liter	drum
	Art.-Nr. 371100	1000 Liter	IBC

Technical Data:

Data	Unit	Method	EUROLUB Gear Fluide AS
Density at 15°C	kg/L	ASTM D 4052	0,848
Viscosity at 40°C	cSt	ASTM D 445	36,6
Viscosity at 100°C	cSt	ASTM D 445	7,2
Viscosityindex (VI)		ASTM D 2270	165
Flash point (COC)	°C	ASTM D 92	212
Pourpoint	°C	ASTM D 6892	-45

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.