

EUROLUB Gear Fluide 6

Description/Applications:	This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared with older Dexron types. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended. The operating instructions of the vehicle and engine manufactures must be followed.
----------------------------------	---

Can be used with:	<p>Aisin Warner JWS 3309(T-IV)/3324(WS)/AW-1 Allison C3/C4, BMW 7045E/8072B/LA2634/Mini C T-IV Cat TO-2, Chrysler Dodge Mopar AS68RC/69RC (T-IV) Chrysler ATF+/-2/+3/+4, Fiat Type IV Daihatsu ATF D-II/D-III SP Ford Mercon LV/Mercon/M2C138-CJ/166-H/922-A1/924-A GM Dexron VI/II/IID/IIE/IIIG/IIIH, TASA Honda Acura DW-1/ATF-Z1(except in CVT) Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR Hyundai/Kia JWS 3314/9683, Isuzu ATF II/III/SP Jaguar ATF 3403 M115/JLM 20238/20292 JASO M315-2013 1A/1A-LV/2A Mazda ATF DII/M-III/M-V/FZ/F-1/S-1/N-1/3317 MB 236.1/2/3/236.5/236.7/236.8/236.9/236.41 Mitsubishi SK/SP-II/SP-III/SP-IV/AW/J2/J3/ATF PA Nissan Matic C/D/J/K/S, Porsche ATF 3403-M115/T-IV Subaru ATF ATF/AW-1/5AT/ATF HP Suzuki ATF 3309/3314/3317/2326/2384K Toyota D-II/D-III/T-III/T-IV/WS VAG G-052-025/052-055/052-162/052-990 VAG G-053-025/055-025/055-162/055-540/060-162 Voith 55.6335.xx (G607), Volvo 97335/97340/1161540 ZF 5HP 18FL/19FL/24A/30/4HP20, ML 05L/09/11A/B/21L</p>
--------------------------	---

Delivery:	Art.-Nr. 370001	12 x 1 Liter	bottle
	Art.-Nr. 370020	20 Liter	can
	Art.-Nr. 370060	60 Liter	hobbock
	Art.-Nr. 370208	208 Liter	drum
	Art.-Nr. 370100	1000 Liter	IBC

Technical Data:

Data	Unit	Method	EUROLUB Gear Fluide 6
Density at 15°C	kg/L	ASTM D 4052	0,843
Viscosity at 40°C	cSt	ASTM D 445	29,6
Viscosity at 100°C	cSt	ASTM D 445	5,90
Viscosityindex (VI)		ASTM D 2270	149
Flash point (COC)	°C	ASTM D 92	212
Pourpoint	°C	ASTM D 6892	-51

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.