

EUROLUB Gear Fluide 8G

Description / Applications:

Gear Fluide 8G is specially formulated for the lubrication of ZF 8HP transmissions. The oil contributes greatly to realizing fuel saving and can be used amongst others in the ZF 8HP transmissions 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions, which are used in various VAG models.

Can be used with:

VAG G 060 162
BMW 8322 2152426 / 2289720 (ATF3+)
Jaguar 02JDE 26444
Land Rover LR023288
Chrysler 68157995AA
Fiat 9.55550-AV5

Delivery:

Art.-Nr. 376001	12 x 1 Liter	bottle
Art.-Nr. 376020	20 Liter	can
Art.-Nr. 376060	60 Liter	hobbock
Art.-Nr. 376208	208 Liter	drum
Art.-Nr. 376100	1000 Liter	IBC

Technical Data:

Data	Unit	Method	EUROLUB Gear Fluide 8G
Density at 15°C	kg/L	ASTM D 4052	0,845
Viscosity at 40°C	cSt	ASTM D 445	25,8
Viscosity at 100°C	cSt	ASTM D 445	6,0
Viscosityindex (VI)		ASTM D 2270	190
Flash point (COC)	°C	ASTM D 92	198
Pourpoint	°C	ASTM D 6892	-45

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.