

EUROLUB 2 TZ Racing

Description / Applications:	<p>2 TZ RACING is a self-mixing two-stroke engine oil.</p> <p>The technical requirements, that is ensuring piston cleanliness and corrosion protection and the prevention of ring sticking, galling and glow ignition, are met by the use of synthetic components with significant reserve.</p> <p>2 TZ RACING is recommended self-mixing according to the manufacturer's instructions for mixing ratios up to 1:100. It is also suitable for use in oil injection (autolube systems).</p>
------------------------------------	--

Can be used with:	<p>API TC Jaso FD ISO-L-EGD Global GD Husqvarna 272 2-Stroke DFI</p>
--------------------------	--

Delivery:	<table> <tr> <td>Art.-Nr. 303001</td> <td>12 x 1 Liter</td> <td>bottle</td> </tr> <tr> <td>Art.-Nr. 303020</td> <td>20 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 303060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 303208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 303100</td> <td>Container</td> <td>IBC</td> </tr> </table>	Art.-Nr. 303001	12 x 1 Liter	bottle	Art.-Nr. 303020	20 Liter	can	Art.-Nr. 303060	60 Liter	hobbock	Art.-Nr. 303208	208 Liter	drum	Art.-Nr. 303100	Container	IBC
Art.-Nr. 303001	12 x 1 Liter	bottle														
Art.-Nr. 303020	20 Liter	can														
Art.-Nr. 303060	60 Liter	hobbock														
Art.-Nr. 303208	208 Liter	drum														
Art.-Nr. 303100	Container	IBC														

Technical Data:

Data	Unit	Method	EUROLUB 2TZ Racing
Density at 15°C	kg/L	D 4052	0,872
Viscosity at 40°C	cSt	D 445	64,6
Viscosity at 100°C	cSt	D 445	9,5
Viscosityindex (VI)		D 2270	129
Flash point (COC)	°C	D 92	116
Pourpoint	°C	D 6892	-24

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.