

## EUROLUB Top 3000 Langzeitfett

|                                     |  |
|-------------------------------------|--|
| <b>Application:<br/>Properties:</b> | Top 3000 long-term grease is a green-fluorescent, semi-synthetic high-performance EP grease with very good adhesion. It is water resistant and very difficult to wash out. |
|-------------------------------------|--|

|                               |           |
|-------------------------------|-----------|
| <b>Designation DIN 51502:</b> | KP 2 G-30 |
|-------------------------------|-----------|

|                                     |  |
|-------------------------------------|--|
| <b>Application recommendations:</b> | <p>Top 3000 long-life grease is suitable for long-term lubrication of heavy construction machinery and agricultural equipment.</p> <ul style="list-style-type: none"> <li>• resistant to oxidation</li> <li>• work stable</li> <li>• extremely water resistant</li> <li>• particularly pronounced anti-corrosion properties</li> <li>• protects against fretting corrosion</li> <li>• high pressure absorption capacity</li> </ul> |
|-------------------------------------|--|

|                  |                 |            |                     |
|------------------|-----------------|------------|---------------------|
| <b>Delivery:</b> | Art.-Nr. 707500 | 30 x 500 g | cartridges          |
|                  | Art.-Nr. 707005 | 5 kg       | plastik hobbock     |
|                  | Art.-Nr. 707015 | 15 kg      | plastik hobbock     |
|                  | Art.-Nr. 707025 | 25 kg      | plastik hobbock     |
|                  | Art.-Nr. 707050 | 50 kg      | sheet metal hobbock |

| <b>Technical Data:</b>                          |              |                  |                             |
|---|--------------|------------------|-----------------------------|
| <b>Data:</b>                                    | <b>Unit:</b> | <b>Method:</b>   | <b>EUROLUB<br/>Top 3000</b> |
| Operating temperature for long-term lubrication | °C           |                  | -30 to +110                 |
| Short time admissible temperature peak value    | °C           |                  | >150                        |
| Worked penetration                              | 1/10 mm      | ASTM D 217       | 265 to 295                  |
| Resistance to water                             |              | DIN ISO 51807-01 | 0-90                        |
| SKF Emcor Test                                  |              | DIN ISO 51802    | 0/0                         |
| Thickener                                       |              |                  | spec. Calcium               |

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

|   |  |
|---|--|
| EUROLUB GmbH<br>Freisinger Strasse 25-27<br>85386 Eching bei München<br>Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 30<br><a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a> | print: 17.10.2017, made 17.10.2017             |
|   | Referenz: spec4978/012017                      |
|   | Name: Top 3000 Langzeitfett PDS_english_707xxx |
|   | Seite 1 von 1                                  |