

EUROLUB HD 5CX Extra SAE 15W/40

Description/Applications:	HD 5CX Extra SAE 15W/40 is suitable for use in both on-road and off-highway applications. This engine oil contributes to low exhaust emission and particle levels benefits highly to the lifetime of emission control systems. This product complies with and exceeds the requirements of API CJ-4. By meeting the requirements of OEM's in Europe and North America this product has a wide choice of application possibilities. This product can be applied in Euro 5 and Euro 6 engines with SCR exhaust gas system and in Euro 3 and Euro 4 engines when indicated by the manufacturer.
----------------------------------	---

Can be used with:	<p>ACEA E9 API CK-4 MB 228.31 MAN M 3575 Volvo VDS-4 Renault VI RLD-3 Deutz DQC III-10 LA Cat ECF-3 Cummins CES 20081 Detroit Diesel 93K218 MTU Type 2.1 Mack EO-O Premium Plus</p>
--------------------------	--

Delivery:	<table> <tr> <td>Art.-Nr. 228020</td> <td>20 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 228060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 228208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 228100</td> <td>Container</td> <td>IBC</td> </tr> </table>	Art.-Nr. 228020	20 Liter	can	Art.-Nr. 228060	60 Liter	hobbock	Art.-Nr. 228208	208 Liter	drum	Art.-Nr. 228100	Container	IBC
Art.-Nr. 228020	20 Liter	can											
Art.-Nr. 228060	60 Liter	hobbock											
Art.-Nr. 228208	208 Liter	drum											
Art.-Nr. 228100	Container	IBC											

Technical Data:

Data	Unit	Method	EUROLUB HD 5CX Extra SAE 15W/40
Density at 15°C	kg/L	D 4052	0,874
Viscosity at 40°C	cSt	D 445	108,7
Viscosity at 100°C	cSt	D 445	14,5
Viscosityindex (VI)		D 2270	137
Flash point (COC)	°C	D 92	232
Pourpoint	°C	D 6892	-36

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.