

EUROLUB Multimax LFD3 SAE 10W/40

| | |
|------------------------------------|---|
| Description / Applications: | This lubricant has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for Euro 3, Euro 4 and Euro 5 engines in combination with different diesel fuel qualities. This engine oil is also suitable for application in engines with or without exhaust catalyts. |
|------------------------------------|---|

| | |
|--------------------------|--|
| Can be used with: | ACEA E4 / E7 API CF MB 228.5 MAN M 3277 Scania LDF-3 / LDF-2 Volvo VDS-3 Renault VI RLD-2 Mack EO-N Deutz DQC III-10 MTU Type 3 |
|--------------------------|--|

| | | | |
|------------------|-----------------|-----------|-------------|
| Delivery: | Art.-Nr. 239020 | 20 liter | plastic can |
| | Art.-Nr. 239060 | 60 liter | hobbock |
| | Art.-Nr. 239208 | 208 liter | drum |
| | Art.-Nr. 239100 | Container | IBC |

Technical Data:

| Data | Unit | Method | EUROLUB Multimax LFD3 SAE 10W/40 |
|---------------------|------|--------|-------------------------------------|
| Density at 15°C | kg/L | D 4052 | 0,863 |
| Viscosity at 40°C | cSt | D 445 | 85,6 |
| Viscosity at 100°C | cSt | D 445 | 13,0 |
| Viscosityindex (VI) | | D 2270 | 152 |
| Flash point (COC) | °C | D 92 | 228 |
| Pourpoint | °C | D 6892 | -36 |

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.