

## EUROLUB EAP 140 Motorinnenschutz

<b>Performance:</b>	EAP 140 Motorinnenschutz creates a highly active nano barrier in the oil which protects all the internal surfaces of engines and equipment such as oil system, manual gearboxes and differentials. Seals, o-rings and shaft seals are kept supple. Improved oil flow during cold start, smoother and quieter engine running, improved performance, extended life of equipment, and excellent “run dry” emergency properties.
---------------------	--

<b>Application:</b>	EAP 140 Motorinnenschutz for use in the oil system of 4-stroke petrol and diesel engines. Applicable for common rail as well as pump injector fuel systems and recommended for engines with turbo charger, catalytic converter and DPF filters. Compatible with all engine oils.
---------------------	--

<b>Directions:</b>	Add to oil system after each oil change. We recommend cleaning the oil system with Oil System Cleaner before use. Observe the maximum oil quantity! In power steering systems, manual transmissions and differentials use at ration 1:10. <b>Note:</b> When using in vehicles with wet clutch, observe the manufacturer’s instructions!
--------------------	--

<b>Delivery:</b>	Art. Nr. 005571      24 x 300 ml EAN-Nr. 4 02537 7005577
------------------	---

<b>Technical Data:</b>	
<b>Density at 20°C</b>	ca. 0,90 – 0,95 g/cm <sup>3</sup>
<b>Flashpoint</b>	>100°C
<b>Further information</b>	Water resistant

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	Druckdatum: 27.11.2017, erstellt am 27.11.2017
	Autor: DW
	Name: EAP 140 Motorinnenschutz PDB_EN
	Seite 1 von 1