

EUROLUB Bio-Kettenöl UWS

Category:	Chain oil
------------------	-----------

Can be used:	CEC-L33-T-82 = 97%
---------------------	--------------------

Product Features: application:	<p>Bio-Kettenöl UWS is a fast biodegradable saw chain oil. It is made from vegetable oils and toxicologically immaculate additives, which do not pollute the environment, because they are degraded there by microorganisms within a short time. Bio chain oil UWS has a very favorable viscosity-temperature behavior, particularly good cold resistance and due to its adhesion and lubrication properties a high protection against wear and corrosion at economical consumption.</p> <p>Shelf life: At least 18 months at -15 ° C to +25 ° C storage temperature. The parameters vary due to raw materials and production within the permissible tolerances.</p>
---	--

Delivery:	Art.-Nr. 539005	4 x 5 Liter	plastic-canister
	Art.-Nr. 539020	20 Liter	plastic-canister
	Art.-Nr. 539060	60 Liter	hobbock
	Art.-Nr. 539208	208 Liter	Drum
	Art.-Nr. 539100	Container	800 – 3.000 Liter per destination

Technical Data:			
Data	Unit	Method	EUROLUB Bio-Kettenöl UWS
Density at 15°C	kg/L	ASTM D 4052	0,933
Viscosity at 40°C	cSt	ASTM D 445	70,0
Flash point (COC)	°C	ASTM D 92	>250
Pourpoint	°C	ASTM D 6892	<-30
Appearance			bright

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.de , info@eurolub.de	print: 15.02.2019, made 15.02.2019
	Referenz: 21820-8D
	Name: Bio-Kettenöl UWS PDS_english_539xxx
	Seite 1 von 1