

EUROLUB Gear LSL SAE 75W/90

Description/Applications:	High-performance gearbox oil for manual gearboxes and axle gears with LS differentials (Limited Slip). It is used for conventional manual gearboxes and axle gears as a multi-functional gearbox oil in passenger cars, heavy-goods vehicles, off-road vehicles and work machines. It can also be used in axle gears with multi-disc locking differentials due to its special additive composition.
----------------------------------	--

Can be used with:	API GL-4 / GL-5 / GL-5 LS (Limited Slip) MIL-L 2105 D
--------------------------	--

Delivery:	Art.-Nr. 383001	12 x 1 Liter	bottle
	Art.-Nr. 383020	20 Liter	can
	Art.-Nr. 383060	60 Liter	hobbock
	Art.-Nr. 383208	208 Liter	drum
	Art.-Nr. 383100	1000 Liter	IBC

Technical Data:

Data	Unit	Method	EUROLUB Gear LSL 75W/90
Density at 15°C	kg/L	ASTM D 4052	0,868
Viscosity at 40°C	cSt	ASTM D 445	82,0
Viscosity at 100°C	cSt	ASTM D 445	17,1
Viscosityindex (VI)		ASTM D 2270	221
Flash point (COC)	°C	ASTM D 92	168
Pourpoint	°C	ASTM D 6892	-36

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.